Extension points in datatable.ini

Settings of datatable.ini that list handlers, classes or directories an extension can add to (1, found by name).

Source file: `doc/eng-us/examples/extension-points/datatable.md` Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/extension-points/datatable.md

Settings of `settings/datatable.ini` whose name says they hold handlers, classes, filters, providers or directories that an extension can add to or replace. **Found by the setting's name: a heuristic.** Read the setting's comment (linked) before relying on it.

An extension adds to a list in its own `settings/datatable.ini.append.php` (active extensions' settings are read after the kernel's and before `settings/override`):

DataTableSettings IgnoreClasses

Shipped: an empty list. The setting.

INI

```ini
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/datatable.ini.append.php
[DataTableSettings]
IgnoreClasses[]=expExampleIgnoreClasse    # your class or value, added to the list
*/ ?>
```

Related

- All extension points
- An extension skeleton
- The blocks of datatable.ini

Generated by `./console exp:help:examples` from `settings/datatable.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.