admininterface.ini [AdditionalMenuSettings]

The settings of [AdditionalMenuSettings] in admininterface.ini: ContextMenuTemplateArray, SubitemsContextMenuTemplateArray, SubMenuTemplateArray, ClassMenuTemplateArray, BookmarkMenuTemplateArray...

Source file: `doc/eng-us/examples/ini-settings/admininterface/AdditionalMenuSettings.md` Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/ini-settings/admininterface/AdditionalMenuSettings.md

The block `[AdditionalMenuSettings]` of `settings/admininterface.ini`, with 9 setting(s).

> Settings to load additional menu items based on templates

Never edit `settings/admininterface.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/admininterface.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/admininterface.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/admininterface.ini.append.php` in an extension (read when the extension is active).

ContextMenuTemplateArray

> Context menu items template(s)

Default: an empty list.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "ContextMenuTemplateArray[]" first replaces the shipped list; without it the items are
 added
ContextMenuTemplateArray[]
*/ ?>
```

SubitemsContextMenuTemplateArray

> Subitems context menu template(s)

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "SubitemsContextMenuTemplateArray[]" first replaces the shipped list; without it the i
tems are added
SubitemsContextMenuTemplateArray[]
*/ ?>
```

SubMenuTemplateArray

> Template(s) for submenus of the popupmenu

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "SubMenuTemplateArray[]" first replaces the shipped list; without it the items are add
ed
SubMenuTemplateArray[]
*/ ?>
```

ClassMenuTemplateArray

> Template(s) for class popup menu on large class icon in node view

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "ClassMenuTemplateArray[]" first replaces the shipped list; without it the items are a
dded
ClassMenuTemplateArray[]
*/ ?>
```

BookmarkMenuTemplateArray

> Template(s) for bookmark popup menu on right side bookmark box

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "BookmarkMenuTemplateArray[]" first replaces the shipped list; without it the items ar
e added
BookmarkMenuTemplateArray[]
*/ ?>
```

AdvancedMenuTemplateArray

> Template(s) for advance menu, sub menu of Context/Subitems menu

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "AdvancedMenuTemplateArray[]" first replaces the shipped list; without it the items ar
e added
AdvancedMenuTemplateArray[]
*/ ?>
```

ExportMenuTemplateArray

> Template(s) for the Export submenu of the advance menu: the items an extension adds below the package entries
> (xrowextract: the CSV entries). Each item opens its tool's form filled in for the node (%nodeID%), never an export
> itself, and is shown only to a user with the tool's policy. Export is shown when it has an item.
> Guide: doc/eng-us/bc/6.0/content-export-menu.md

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "ExportMenuTemplateArray[]" first replaces the shipped list; without it the items are
added
ExportMenuTemplateArray[]
*/ ?>
```

ExportSubMenuTemplateArray

> Template(s) for the submenus of those items (a level below Export), output after the Export menu

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "ExportSubMenuTemplateArray[]" first replaces the shipped list; without it the items a
re added
ExportSubMenuTemplateArray[]
*/ ?>
```

ImportExportMenuTemplateArray

> Template(s) for the import and job items of the Import/Export menu (Import/Export only).
> Declared empty so the
> popup_export_items.tpl reads it without a missing-variable error when no extension adds one.

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[AdditionalMenuSettings]
# an empty "ImportExportMenuTemplateArray[]" first replaces the shipped list; without it the item
s are added
ImportExportMenuTemplateArray[]
*/ ?>
```

Related

- All blocks of admininterface.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/admininterface.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.