debug.ini [DebugSettings]

The settings of [DebugSettings] in debug.ini: ConditionDebug

Source file: `doc/eng-us/examples/ini-settings/debug/DebugSettings.md` Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/ini-settings/debug/DebugSettings.md

The block `[DebugSettings]` of `settings/debug.ini`, with 1 setting(s).

Never edit `settings/debug.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/debug.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/debug.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/debug.ini.append.php` in an extension (read when the extension is active).

ConditionDebug

> Master switch for conditional debugging, if disabled
> no conditions are checked.

Default: `enabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[DebugSettings]
ConditionDebug=enabled
*/ ?>
```

Related

- All blocks of debug.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/debug.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.