debug.ini [GeneralCondition]

The settings of [GeneralCondition] in debug.ini: workflow-event, workflow-process, workflow-type, kernel-workflow-approve, kernel-content-view, kernel-content-view-cache, kernel-content-class, kernel-content-treenode ...

Source file: `doc/eng-us/examples/ini-settings/debug/GeneralCondition.md` Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/ini-settings/debug/GeneralCondition.md

The block `[GeneralCondition]` of `settings/debug.ini`, with 42 setting(s).

Never edit `settings/debug.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/debug.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/debug.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/debug.ini.append.php` in an extension (read when the extension is active).

workflow-event

> Enabled/disabled specific conditions
> Default is to have everything off and to turn it on
> in override files.

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
workflow-event=disabled
*/ ?>
```

workflow-process

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
workflow-process=disabled
*/ ?>
```

workflow-type

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
workflow-type=disabled
*/ ?>
```

kernel-workflow-approve

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-workflow-approve=disabled
*/ ?>
```

kernel-content-view

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-view=disabled
*/ ?>
```

kernel-content-view-cache

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-view-cache=disabled
*/ ?>
```

kernel-content-class

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-class=disabled
*/ ?>
```

kernel-content-treenode

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-treenode=disabled
*/ ?>
```

kernel-content-object-copy

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-object-copy=disabled
*/ ?>
```

kernel-content-object-related-objects

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-object-related-objects=disabled
*/ ?>
```

kernel-content-object-limitation

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-object-limitation=disabled
*/ ?>
```

kernel-content-edit

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-edit=disabled
*/ ?>
```

kernel-content-publish

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-content-publish=disabled
*/ ?>
```

kernel-persistent-object-cache

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-persistent-object-cache=disabled
*/ ?>
```

kernel-urltranslator

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-urltranslator=disabled
*/ ?>
```

kernel-search-ezsearch

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-search-ezsearch=disabled
*/ ?>
```

kernel-search-openfts

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-search-openfts=disabled
*/ ?>
```

kernel-policy-limitation

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-policy-limitation=disabled
*/ ?>
```

kernel-role-edit

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-role-edit=disabled
*/ ?>
```

kernel-siteaccess

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-siteaccess=disabled
*/ ?>
```

kernel-db-postgresql

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-db-postgresql=disabled
*/ ?>
```

kernel-user

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-user=disabled
*/ ?>
```

kernel-notification

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-notification=disabled
*/ ?>
```

kernel-ssl-zone

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-ssl-zone=disabled
*/ ?>
```

kernel-clustering

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-clustering=disabled
*/ ?>
```

kernel-ezpackage-store

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
kernel-ezpackage-store=disabled
*/ ?>
```

module-run

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
module-run=disabled
*/ ?>
```

collaboration-group-tree

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
collaboration-group-tree=disabled
*/ ?>
```

collaboration-item-list

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
collaboration-item-list=disabled
*/ ?>
```

eztemplate-tree-cache

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
eztemplate-tree-cache=disabled
*/ ?>
```

eztemplate-compile

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
eztemplate-compile=disabled
*/ ?>
```

i18n-tstranslator

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
i18n-tstranslator=disabled
*/ ?>
```

ezfile-create

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
ezfile-create=disabled
*/ ?>
```

lib-ezfile-seek

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezfile-seek=disabled
*/ ?>
```

lib-ezfile-openclose

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezfile-openclose=disabled
*/ ?>
```

lib-ezfile-readwrite

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezfile-readwrite=disabled
*/ ?>
```

lib-ezfile-copy

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezfile-copy=disabled
*/ ?>
```

lib-ezfile-gziplibz

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezfile-gziplibz=disabled
*/ ?>
```

lib-ezimage-shell

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezimage-shell=disabled
*/ ?>
```

lib-dbschema-transformation

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-dbschema-transformation=disabled
*/ ?>
```

lib-ezutil-web

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezutil-web=disabled
*/ ?>
```

lib-ezutils-dir

Default: `disabled`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/debug.ini.append.php
[GeneralCondition]
lib-ezutils-dir=disabled
*/ ?>
```

Related

- All blocks of debug.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/debug.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.