/content/versionview

The view content/versionview: its address, parameters and the policy functions it needs.

Source file: doc/eng-us/examples/module-views/content/versionview.md Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/module-views/content/versionview.md

A view of the `content` module, defined in `kernel/content/module.php` and run by `kernel/content/versionview.php`.

Address

```
/content/versionview/<ObjectID>/<EditVersion>/<LanguageCode>/<FromLanguage>/(language)/<Language>
/(offset)/<Offset>/(site_access)/<SiteAccess>/(view_mode)/<ViewMode>
```

Ordered parameters, in this order after the view name: `ObjectID`, `EditVersion`, `LanguageCode`, `FromLanguage`.

Unordered parameters, in any order as `/(name)/value`: `(language)` sets `Language`, `(offset)` sets `Offset`, `(site_access)` sets `SiteAccess`, `(view_mode)` sets `ViewMode`.

Who may open it

The user needs this policy function:

- `content/versionread`

A policy on `content/*` (every function) also grants it; limitations of the policy (section, subtree, class ...) still apply where the view checks them.

Details

Key	Value
Navigation part	`ezcontentnavigationpart`
UI context	`edit`
Single POST actions	ChangeSettingsButton: ChangeSettings, EditButton: Edit, VersionsButton: Versions, PreviewPublishButton: Publish, PreviewPublishNotNotifyButton: Publish
POST action parameters	ChangeSettings (Language: SelectedLanguage, PlacementID: SelectedPlacement, SiteAccess: SelectedSiteAccess, ViewMode: SelectedViewMode)

Example

A link in a template (`ezurl` adds the siteaccess and quotes the address); the parameter values are placeholders:

Template

```
<a href={'/content/versionview/1/1/languagecode/fromlanguage'|ezurl}>content/versionview</a>
<a href={concat( '/content/versionview/1/1/languagecode/fromlanguage/(language)/', 1 )|ezurl}>con
tent/versionview</a>
```

From PHP, the redirect a view gives after it has done its work:

PHP

```
return $Module->redirectTo( '/content/versionview/1/1/languagecode/fromlanguage' );
```

Related

- All views of content
- The policies of content
- A custom module and view

Generated by `./console exp:help:examples` from `kernel/content/module.php`, `kernel/content/versionview.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.