/setup/logs

The view setup/logs: its address, parameters and the policy functions it needs.

Source file: doc/eng-us/examples/module-views/setup/logs.md Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/module-views/setup/logs.md

A view of the `setup` module, defined in `kernel/setup/module.php` and run by `kernel/setup/logs.php`.

Address

```
/setup/logs/<Mode>/<Key>/(rotation)/<rotation>/(level)/<level>/(search)/<search>/(regex)/<regex>/
(case)/<case>/(from)/<from>/(to)/<to>/(siteaccess)/<siteaccess>/(uri)/<uri>/(ip)/<ip>/(reference)
/<reference>/(scope)/<scope>/(rotations)/<rotations>/(cursor)/<cursor>/(offset)/<offset>/(follow)
/<follow>/(wrap)/<wrap>/(unmask)/<unmask>/(done)/<done>/(ok)/<ok>/(archive)/<archive>
```

Ordered parameters, in this order after the view name: `Mode`, `Key`.

Unordered parameters, in any order as `/(name)/value`: `(rotation)` sets `rotation`, `(level)` sets `level`, `(search)` sets `search`, `(regex)` sets `regex`, `(case)` sets `case`, `(from)` sets `from`, `(to)` sets `to`, `(siteaccess)` sets `siteaccess`, `(uri)` sets `uri`, `(ip)` sets `ip`, `(reference)` sets `reference`, `(scope)` sets `scope`, `(rotations)` sets `rotations`, `(cursor)` sets `cursor`, `(offset)` sets `offset`, `(follow)` sets `follow`, `(wrap)` sets `wrap`, `(unmask)` sets `unmask`, `(done)` sets `done`, `(ok)` sets `ok`, `(archive)` sets `archive`.

Who may open it

The user needs this policy function:

- `setup/logs`

A policy on `setup/*` (every function) also grants it; limitations of the policy (section, subtree, class ...) still apply where the view checks them.

Details

Key	Value
Navigation part	`ezsetupnavigationpart`
UI context	`administration`

Example

A link in a template (`ezurl` adds the siteaccess and quotes the address); the parameter values are placeholders:

Template

```
<a href={'/setup/logs/mode/key'|ezurl}>setup/logs</a>
<a href={concat( '/setup/logs/mode/key/(rotation)/', 1 )|ezurl}>setup/logs</a>
```

From PHP, the redirect a view gives after it has done its work:

PHP

```php
return $Module->redirectTo( '/setup/logs/mode/key' );
```

Related

- All views of setup
- The policies of setup
- A custom module and view

Generated by `./console exp:help:examples` from `kernel/setup/module.php`, `kernel/setup/logs.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.