/trigger/list

The view trigger/list: its address, parameters and the policy functions it needs.

Source file: doc/eng-us/examples/module-views/trigger/list.md Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/module-views/trigger/list.md

A view of the `trigger` module, defined in `kernel/trigger/module.php` and run by `kernel/trigger/list.php`.

Address

```
/trigger/list
```

Who may open it

The view names no policy function, so the user needs a policy for the whole module: `trigger/*` (every function of the module) in one of the roles assigned to them.

Details

Key	Value
Navigation part	ezsetupnavigationpart
UI context	administration

Example

A link in a template (`ezurl` adds the siteaccess and quotes the address); the parameter values are placeholders:

Template

```
<a href={'/trigger/list'|ezurl}>trigger/list</a>
```

From PHP, the redirect a view gives after it has done its work:

PHP

```
return $Module->redirectTo( '/trigger/list' );
```

Related

- All views of trigger
- The policies of trigger
- A custom module and view

Generated by `./console exp:help:examples` from `kernel/trigger/module.php`,

`kernel/trigger/list.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.