/user/deactivate

The view user/deactivate: its address, parameters and the policy functions it needs.

Source file: doc/eng-us/examples/module-views/user/deactivate.md Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/module-views/user/deactivate.md

A view of the `user` module, defined in `kernel/user/module.php` and run by `kernel/user/deactivate.php`.

Address

```
/user/deactivate
```

Who may open it

The user needs this policy function:

- `user/deactivate`

A policy on `user/*` (every function) also grants it; limitations of the policy (section, subtree, class ...) still apply where the view checks them.

Details

Key	Value
Navigation part	`ezusernavigationpart`
UI context	`administration`

Example

A link in a template (`ezurl` adds the siteaccess and quotes the address); the parameter values are placeholders:

Template

```
<a href={'/user/deactivate'|ezurl}>user/deactivate</a>
```

From PHP, the redirect a view gives after it has done its work:

PHP

```
return $Module->redirectTo( '/user/deactivate' );
```

Related

- All views of user
- The policies of user
- A custom module and view

Generated by `./console exp:help:examples` from `kernel/user/module.php`, `kernel/user/deactivate.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.