default template function

The default template function, registered by eZTemplateSetFunction.

Source file: `doc/eng-us/examples/template-functions/default.md` Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/template-functions/default.md

The default template function

Registered in `lib/eztemplate/classes/eztemplateautoload.php` by the class `eZTemplateSetFunction` (`lib/eztemplate/classes/eztemplatesetfunction.php`). The same class also handles: set, let.

In a shipped template

The first use in the templates of this installation, `benchmarks/eztemplate/mark.tpl` line 42:

Template

```
{default d=42}
```

Related

- All template functions
- Template operators
- Templates and design

Generated by `./console exp:help:examples` from `lib/eztemplate/classes/eztemplateautoload.php`, `lib/eztemplate/classes/eztemplatesetfunction.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.