module_params template operator

The module_params template operator: no named parameters, registered by eZModuleParamsOperator.

Source file: doc/eng-us/examples/template-operators/module_params.md Last changed 2026-11-04
https://doc.exponential.earth/exphelp/viewer/examples/template-operators/module_params.md

The module_params template operator

Registered in `kernel/common/eztemplateautoload.php` by the class `eZModuleParamsOperator` (`kernel/common/ezmoduleparamsoperator.php`).

Parameters

None.

Example

Built from the parameter list above; the values are placeholders (the operator's template hints decide whether it takes an input).

Template

```
{$value|module_params}
```

In a shipped template

The first use in the templates of this installation, `design/admin/templates/parts/content/menu.tpl` line 3:

Template

```
{if ne(module_params().module_name, 'error')}
```

Related

- All template operators
- Templates and design
- A custom template operator

Generated by `./console exp:help:examples` from `kernel/common/eztemplateautoload.php`, `kernel/common/ezmoduleparamsoperator.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.