exp:expmigrationrecordstop

Source file: doc/eng-us/examples/commands/expmigrationrecordstop.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/commands/expmigrationrecordstop.md

Stop a recording of changes: the one named, a user's own (--user) or the site-wide window (--site-wide); its events stay for exp:migration:generate --from-recording; a dry run unless --apply.

Script `bin/php/expmigrationrecordstop.php`, code in `kernel/private/classes/commands/expmigrationrecordstop.php`. Run it from the installation root, as the user the web server runs as:

Shell

```
./console exp:expmigrationrecordstop --help
./console exp:migration:record:stop --help
php bin/php/expmigrationrecordstop.php --help
```

Help text

```
Stop a recording of changes
Stops the recording named by its id, or else the session recording of --user (default: [RunSettin
gs]
RunAsUser), or with --site-wide the site-wide window. Nothing more is recorded; what was recorded
 stays
until exp:migration:record:discard, for exp:migration:record:show and exp:migration:generate
--from-recording. Without --apply it says what it would stop.

./console exp:migration:record:stop --apply
./console exp:migration:record:stop --site-wide --apply
./console exp:migration:record:stop 20261101-120000-a1b2c3 --apply
```

Options

Option	Value	Help
`--apply`		Make the changes (the default is a dry run that lists them and changes nothing)
`--dry-run`		The default, accepted for scripts that pass it: list what would change, change nothing
`--format`	required	text (default) or json (the machine output exp-migration/1)
`--site-wide`		The site-wide recording: every change of every user and of the console (without it: one user's own changes)
`--user`	required	The user, by login, whose own changes a session recording keeps (default: [RunSettings] RunAsUser of migration.ini)

Read from the option definitions in the code (`startup()`, `getOptions()`, `options()` or `ezcConsoleOption`). Every script also takes the standard options of the script framework (`--help`, `--siteaccess`, `--debug`, `--quiet`, `--allow-root-user` ...).

Arguments: `[recording]`.

Related

- All console commands

Generated by `./console exp:help:examples` from `bin/php/expmigrationrecordstop.php`, `kernel/private/classes/commands/expmigrationrecordstop.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.