exp:expstaticdiff

Source file: `doc/ger-de/beispiele/befehle/expstaticdiff.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/commands/expstaticdiff.md

Was der letzte statische Build eines Ziels geändert hat, ob sein Ordner noch zum Manifest passt und ob jeder Link darin funktioniert, wenn er unterhalb eines Pfads ausgeliefert wird.

Skript `bin/php/expstaticdiff.php`, Code in `kernel/private/classes/commands/expstaticdiff.php`. Führen Sie es im Wurzelverzeichnis der Installation aus, als der Benutzer, unter dem der Webserver läuft:

Shell

```
./console exp:expstaticdiff --help
./console exp:static:diff --help
php bin/php/expstaticdiff.php --help
```

Hilfetext

Was `--help` ausgibt, so wie der Befehl es schreibt:

```
What the last static build changed
Compares the manifest of the target's folder with the one of the build before it: the files added
,
changed and removed. --verify compares the folder with its manifest (files missing, changed since
 the
build, or not listed); --check-links checks every link and file as a browser would, served below
each
--mount. Changes nothing; exit 1 when --verify or --check-links finds a problem.

./console exp:static:diff github-public
./console exp:static:diff github-public --verify
./console exp:static:diff github-public --check-links --mount=/ --mount=/my-site/
```

Optionen

Option	Wert	Hilfe
`--format`	erforderlich	text (Standard) oder json (die Maschinenausgabe exp-static/1)
`--verify`		Den Ordner mit seinem Manifest vergleichen: fehlende Dateien, seit dem Build geänderte oder nicht aufgeführte
`--check-links`		Jeden Link und jede Datei des Ordners prüfen, wie ein Browser es täte, ausgeliefert unterhalb jedes --mount
`--mount`	erforderlich	Der Pfad, unter dem der Ordner für --check-links ausgeliefert wird (Standard BasePath des Ziels; eine Kommaliste oder wiederholt: /,/repo/)

Aus den Optionsdefinitionen im Code gelesen (`startup()`, `getOptions()`, `options()` oder `ezcConsoleOption`). Jedes Skript nimmt außerdem die Standardoptionen des Skript-Frameworks (`--help`, `--siteaccess`, `--debug`, `--quiet`, `--allow-root-user` …).

Argumente: `[target]`.

Siehe auch

- Alle Konsolenbefehle

Erzeugt von `./console exp:help:examples --language=ger-de` aus `bin/php/expstaticdiff.php`, `kernel/private/classes/commands/expstaticdiff.php`. Bearbeiten Sie diese Seite nicht: Ändern Sie die Quelle oder die deutsche Übersetzung und erzeugen Sie sie neu (wie). Freie Dokumentation: GFDL 1.3 oder später.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.