exp:expusersessions

Source file: doc/eng-us/examples/commands/expusersessions.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/commands/expusersessions.md

The tracked sessions of an account (Your devices): list them, end all of them or one, as an administrator does on user/sessions (ending is a dry run unless --apply).

Script `bin/php/expusersessions.php`, code in `kernel/private/classes/commands/expusersessions.php`. Run it from the installation root, as the user the web server runs as:

Shell

```
./console exp:expusersessions --help
./console exp:user:sessions --help
php bin/php/expusersessions.php --help
```

Help text

```
The sessions of an account
Lists the account's running sessions as Your devices shows them: id, how it signed in, device and
browser, the approximate address and the last activity. --end ends all of them, --session=<id>
ends one, as an administrator does on user/sessions; the person has to sign in again there. The
audit records access.session.revoke. Without --apply nothing is ended.

./console exp:user:sessions jane
./console exp:user:sessions jane --end --apply
./console exp:user:sessions jane --session=812 --apply
```

Options

Option	Value	Help
`--end`		End every tracked session of the account (Your devices)
`--session`	required	End only the session with this id (from the list)
`--apply`		Make the change; without it the command only lists what it would change (a dry run)
`--dry-run`		The default, kept for scripts that pass it: list what would change, change nothing
`--as`	required	Act as this user (login, e-mail or id; default the user of [UserSettings] UserCreatorID); the audit records it as who did it
`--format`	required	text (default) or json (the machine output exp-user/1)

Read from the option definitions in the code (`startup()`, `getOptions()`, `options()` or `ezcConsoleOption`). Every script also takes the standard options of the script framework (`--help`, `--siteaccess`, `--debug`, `--quiet`, `--allow-root-user` ...).

Arguments: `[user]`.

Related

- All console commands

Generated by `./console exp:help:examples` from `bin/php/expusersessions.php`, `kernel/private/classes/commands/expusersessions.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.