Extension points in content.ini

Settings of content.ini that list handlers, classes or directories an extension can add to (34, found by name).

Source file: doc/eng-us/examples/extension-points/content.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/extension-points/content.md

Settings of `settings/content.ini` whose name says they hold handlers, classes, filters, providers or directories that an extension can add to or replace. **Found by the setting's name: a heuristic.** Read the setting's comment (linked) before relying on it.

An extension adds to a list in its own `settings/content.ini.append.php` (active extensions' settings are read after the kernel's and before `settings/override`):

VersionManagement VersionHistoryClass

Shipped: a hash of 1: `1=75`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[VersionManagement]
VersionHistoryClass[expexample]=expExampleVersionHistoryClas    # key and value are yours
*/ ?>
```

EditSettings ExtensionDirectories

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[EditSettings]
ExtensionDirectories[]=expExampleExtensionDirectorie    # your class or value, added to the list
*/ ?>
```

DataTypeSettings ExtensionDirectories

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[DataTypeSettings]
ExtensionDirectories[]=expExampleExtensionDirectorie    # your class or value, added to the list
*/ ?>
```

ActionSettings ExtensionDirectories

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[ActionSettings]
ExtensionDirectories[]=expExampleExtensionDirectorie    # your class or value, added to the list
*/ ?>
```

header AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[header]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

paragraph AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[paragraph]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

table AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[table]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

tr AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[tr]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

td AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[td]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

th AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[th]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

literal AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[literal]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

strong AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[strong]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

emphasize AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[emphasize]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

ol AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[ol]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

ul AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[ul]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

link AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[link]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

object AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[object]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

embed AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[embed]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

embed-inline AvailableClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[embed-inline]
AvailableClasses[]=expExampleAvailableClasse    # your class or value, added to the list
*/ ?>
```

RelationGroupSettings ImagesClassList

Shipped: a list of 1: `image`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[RelationGroupSettings]
ImagesClassList[]=expExampleImagesClass    # your class or value, added to the list
*/ ?>
```

RelationGroupSettings FilesClassList

Shipped: a list of 1: `file`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[RelationGroupSettings]
FilesClassList[]=expExampleFilesClass    # your class or value, added to the list
*/ ?>
```

UnpublishSettings ClassList

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[UnpublishSettings]
ClassList[]=expExampleClass    # your class or value, added to the list
*/ ?>
```

HideSettings ReverseRelationCheck

Shipped: `warn`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[HideSettings]
ReverseRelationCheck=warn    # replace with your class or value
*/ ?>
```

FetchFunctionSettings InstClassListFilter

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[FetchFunctionSettings]
InstClassListFilter[]=expExampleInstClassListFilter    # your class or value, added to the list
*/ ?>
```

NamePatternSettings ResolverClasses

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[NamePatternSettings]
ResolverClasses[]=expExampleResolverClasse    # your class or value, added to the list
*/ ?>
```

RemoveSettings ShowRemoveToTrashCheck

Shipped: `true`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[RemoveSettings]
ShowRemoveToTrashCheck=true    # replace with your class or value
*/ ?>
```

RemoveSettings ReverseRelationCheck

Shipped: `warn`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[RemoveSettings]
ReverseRelationCheck=warn    # replace with your class or value
*/ ?>
```

ReverseRelationSettings ProviderClassList

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[ReverseRelationSettings]
ProviderClassList[]=expExampleProviderClass    # your class or value, added to the list
*/ ?>
```

ReviewHoldSettings AutoHoldClassList

Shipped: a list of 1: `comment`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[ReviewHoldSettings]
AutoHoldClassList[]=expExampleAutoHoldClass    # your class or value, added to the list
*/ ?>
```

AlphabeticalFilterSettings ContentFilterList

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[AlphabeticalFilterSettings]
ContentFilterList[]=expExampleContentFilter    # your class or value, added to the list
*/ ?>
```

PublishingSettings AsynchronousPublishingFilters

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[PublishingSettings]
AsynchronousPublishingFilters[]=expExampleAsynchronousPublishingFilter    # your class or value,
added to the list
*/ ?>
```

PublishingSettings AsynchronousPublishingPreQueueHooks

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[PublishingSettings]
AsynchronousPublishingPreQueueHooks[]=expExampleAsynchronousPublishingPreQueueHook    # your clas
s or value, added to the list
*/ ?>
```

PublishingSettings AsynchronousPublishingPostHandlingHooks

Shipped: an empty list. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[PublishingSettings]
AsynchronousPublishingPostHandlingHooks[]=expExampleAsynchronousPublishingPostHandlingHook    # y
our class or value, added to the list
*/ ?>
```

TestingSettings MultivariateTestingHandlerClass

Shipped: `ezpMultivariateTestHandler`. The setting.

INI

```
<?php /* #?ini charset="utf-8"?
# extension/expexample/settings/content.ini.append.php
[TestingSettings]
MultivariateTestingHandlerClass=ezpMultivariateTestHandler    # replace with your class or value
*/ ?>
```

Related

- All extension points
- An extension skeleton

- The blocks of content.ini

Generated by `./console exp:help:examples` from `settings/content.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.