fetch('content', 'list_count')

The fetch function list_count of the content module: 13 parameter(s), 1 required.

Source file: doc/eng-us/examples/fetch-functions/content/list_count.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/fetch-functions/content/list_count.md

Defined in `kernel/content/function_definition.php`; it calls `eZContentFunctionCollection::fetchObjectTreeCount()` (`kernel/content/ezcontentfunctioncollection.php`). Operation type: read.

Parameters

Parameter	Type	Required	Default
parent_node_id	integer	yes	
only_translated	bool	no	false
language	string	no	false
class_filter_type	string	no	false
class_filter_array	array	no	false
attribute_filter	mixed	no	false
depth	string	no	1
depth_operator	string	no	'le'
ignore_visibility	bool	no	false
limitation	array	no	null
main_node_only	bool	no	false
extended_attribute_filter	mixed	no	false
objectname_filter	string	no	null

Example

In a template (the values are placeholders of each parameter's type):

Template

```
{def $result = fetch( 'content', 'list_count', hash( 'parent_node_id', 1 ) )}
{* with every parameter *}
{def $all = fetch( 'content', 'list_count', hash( 'parent_node_id', 1,
                                                  'only_translated', true(),
                                                  'language', 'language',
                                                  'class_filter_type', 'class_filter_type',
                                                  'class_filter_array', array(),
                                                  'attribute_filter', $attribute_filter,
                                                  'depth', 1,
                                                  'depth_operator', 'le',
                                                  'ignore_visibility', true(),
                                                  'limitation', array(),
                                                  'main_node_only', true(),
                                                  'extended_attribute_filter', $extended_attribute_fil
ter,
                                                  'objectname_filter', 'objectname_filter' ) )}
```

In PHP, the same function through the function handler (`lib/ezutils/classes/ezfunctionhandler.php`):

PHP

```
$result = eZFunctionHandler::execute( 'content', 'list_count', array( 'parent_node_id' => 1 ) );
```

In a shipped template

The first use in the templates of this installation, `design/base/override/templates/full/forum.tpl` line 1:

Template

```
{let topic_count=fetch('content','list_count',hash(parent_node_id,$node.node_id))}
```

Related

- All fetch functions of content
- The views of the content module
- The fetch template operator

Generated by `./console exp:help:examples` from `kernel/content/function_definition.php`, `kernel/content/ezcontentfunctioncollection.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.