fetch('content', 'reverse_related_objects')

The fetch function reverse_related_objects of the content module: 10 parameter(s), 1 required.

Source file: doc/eng-us/examples/fetch-functions/content/reverse_related_objects.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/fetch-functions/content/reverse_related_objects.md

Defined in `kernel/content/function_definition.php`; it calls `eZContentFunctionCollection::fetchReverseRelatedObjects()` (`kernel/content/ezcontentfunctioncollection.php`). Operation type: read.

Parameters

Parameter	Type	Required	Default
`object_id`	integer	yes	
`attribute_identifier`	string	no	
`all_relations`	boolean	no	`false`
`group_by_attribute`	boolean	no	`false`
`sort_by`	array	no	`array()`
`ignore_visibility`	boolean	no	`null`
`limit`	integer	no	`false`
`offset`	integer	no	`false`
`as_object`	boolean	no	`true`
`load_data_map`	boolean	no	`false`

Example

In a template (the values are placeholders of each parameter's type):

Template

```
{def $result = fetch( 'content', 'reverse_related_objects', hash( 'object_id', 1 ) )}
{* with every parameter *}
{def $all = fetch( 'content', 'reverse_related_objects', hash( 'object_id', 1,
                                                               'attribute_identifier', 'attribute_iden
tifier',
                                                               'all_relations', true(),
                                                               'group_by_attribute', true(),
                                                               'sort_by', array(),
                                                               'ignore_visibility', true(),
                                                               'limit', 1,
                                                               'offset', 1,
                                                               'as_object', true(),
                                                               'load_data_map', true() ) )}
```

In PHP, the same function through the function handler (`lib/ezutils/classes/ezfunctionhandler.php`):

PHP

```
$result = eZFunctionHandler::execute( 'content', 'reverse_related_objects', array( 'object_id' =>
 1 ) );
```

In a shipped template

The first use in the templates of this installation, `design/admin/templates/relations.tpl` line 79:

Template

```
{def $reverse_related_objects_grouped = fetch( 'content', 'reverse_related_objects', hash( 'objec
t_id', $node.object.id, 'all_relations', true(), 'group_by_attribute', true(), 'sort_by', array(
array( 'class_identifier', true() ), array( 'name', true() ) ), 'limit', $page_limit, 'offset', $
offset ) )}
```

Related

- All fetch functions of content
- The views of the content module
- The fetch template operator

Generated by `./console exp:help:examples` from `kernel/content/function_definition.php`, `kernel/content/ezcontentfunctioncollection.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.