fetch('setup', 'database_version')

Die Fetch-Funktion database_version des Moduls setup: 1 Parameter, 0 erforderlich.

Source file: doc/ger-de/beispiele/fetch-funktionen/setup/database_version.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/fetch-functions/setup/database_version.md

Definiert in `kernel/setup/function_definition.php`; sie ruft `eZSetupFunctionCollection::fetchDatabaseVersion()` auf (`kernel/setup/ezsetupfunctioncollection.php`). Operationstyp: read.

Parameter

Parameter	Typ	Erforderlich	Standard
`with_release`	bool	nein	`true`

Beispiel

In einem Template (die Werte sind Platzhalter vom Typ des jeweiligen Parameters):

Template

```
{def $result = fetch( 'setup', 'database_version', hash( 'with_release', true() ) )}
```

In PHP dieselbe Funktion über den Function-Handler (`lib/ezutils/classes/ezfunctionhandler.php`):

PHP

```
$result = eZFunctionHandler::execute( 'setup', 'database_version', array( 'with_release' => true
) );
```

Siehe auch

- Alle Fetch-Funktionen von setup
- Die Ansichten des Moduls setup
- Der Template-Operator fetch

Erzeugt von `./console exp:help:examples --language=ger-de` aus `kernel/setup/function_definition.php`, `kernel/setup/ezsetupfunctioncollection.php`. Bearbeiten Sie diese Seite nicht: Ändern Sie die Quelle oder die deutsche Übersetzung und erzeugen Sie sie neu (wie). Freie Dokumentation: GFDL 1.3 oder später.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.