fetch('setup', 'state')

The fetch function state of the setup module: 0 parameter(s), 0 required.

Source file: doc/eng-us/examples/fetch-functions/setup/state.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/fetch-functions/setup/state.md

Defined in `kernel/setup/function_definition.php`; it calls `eZSetupFunctionCollection::fetchState()` (`kernel/setup/ezsetupfunctioncollection.php`). Operation type: read.

Parameters

None.

Example

In a template (the values are placeholders of each parameter's type):

Template

```
{def $result = fetch( 'setup', 'state' )}
```

In PHP, the same function through the function handler (`lib/ezutils/classes/ezfunctionhandler.php`):

PHP

```
$result = eZFunctionHandler::execute( 'setup', 'state', array() );
```

Related

- All fetch functions of setup
- The views of the setup module
- The fetch template operator

Generated by `./console exp:help:examples` from `kernel/setup/function_definition.php`, `kernel/setup/ezsetupfunctioncollection.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.