admininterface.ini [WindowControlsSettings]

The settings of [WindowControlsSettings] in admininterface.ini: HiddenTabs, AdditionalTabs

Source file: doc/eng-us/examples/ini-settings/admininterface/WindowControlsSettings.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/admininterface/WindowControlsSettings.md

The block `[WindowControlsSettings]` of `settings/admininterface.ini`, with 2 setting(s).

> Settings used by window controls template

Never edit `settings/admininterface.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/admininterface.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/admininterface.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/admininterface.ini.append.php` in an extension (read when the extension is active).

HiddenTabs

> Additional tabs the node view leaves out, whatever AdditionalTabs[] says: a siteaccess cannot take a tab out of AdditionalTabs[] that an extension appends (extension settings are read after the siteaccess's). The editor siteaccess hides the Layouts tab with it.

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[WindowControlsSettings]
# an empty "HiddenTabs[]" first replaces the shipped list; without it the items are added
HiddenTabs[]
*/ ?>
```

AdditionalTabs

> List of additional tab identifiers
> AdditionalTabs[]=customtab
> The audit trail of a node (doc/eng-us/bc/6.0/audit.md, "Placement"), only with audit/read
> The rows of data tables that point at a node or its object (doc/eng-us/features/6.0/data-tables.md, "Relations"), only with datatable/read and only when there are some

Default: a list of 4: `roles`, `policies`, `audit`, `datatable`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/admininterface.ini.append.php
[WindowControlsSettings]
# an empty "AdditionalTabs[]" first replaces the shipped list; without it the items are added
AdditionalTabs[]
AdditionalTabs[]=roles
AdditionalTabs[]=policies
AdditionalTabs[]=audit
AdditionalTabs[]=datatable
*/ ?>
```

Related

- All blocks of admininterface.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/admininterface.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.