datatable.ini

The blocks and settings of datatable.ini.

Source file: `doc/eng-us/examples/ini-settings/datatable/README.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/datatable/README.md

The shipped settings of `settings/datatable.ini`: 3 blocks, 10 settings.

> Data tables: the tables of the installation's persistent classes (eZPersistentObject), the named database
> connections they and the tools can use, their schema, their relations to content, and the synchronisation between
> tables and content. See doc/eng-us/features/6.0/data-tables.md.
>
> Connections made in the administration (Setup > Data tables > Connections) are rows of the table
> exp_data_connection and need nothing here. This file is for what an extension ships: a connection it declares, the
> connection one of its classes uses, a relation its definition() does not state.

Block	Settings
DataTableSettings	5
ConnectionSettings	4
ClassSettings	1

- All examples

Generated by `./console exp:help:examples` from `settings/datatable.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.