# error.ini [HTTPError-404]

The settings of [HTTPError-404] in error.ini: HTTPName, HeaderList

Source file: `doc/eng-us/examples/ini-settings/error/HTTPError-404.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/error/HTTPError-404.md

The block `[HTTPError-404]` of `settings/error.ini`, with 2 setting(s).

> Definition for the HTTP error code 404.
> It's possible to specify more error codes by creating a group called
> HTTPError followed by a - (dash) and the HTTP error code.
> The group most contain the HTTPName variable, if not the error code
> is not issued to the browser.
> Note: The HTTPName must be contain the correct string for the
> specific HTTP error code.
>
> HeaderList[] adds response headers to the error page, one per entry:
> HeaderList[<header name>]=<value>. They are sent after the status lines,
> and stored with the page in the content view cache, so a cached error page
> sends them again. A name that is not a valid header name, or a value with a
> line break, is left out with a warning. HeaderList[Status]=<text> is read
> as HTTPName when HTTPName is not set. Empty by default: nothing is added.
> Example:
> HeaderList[Cache-Control]=public, must-revalidate, max-age=300

Never edit `settings/error.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/error.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/error.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/error.ini.append.php` in an extension (read when the extension is active).

## HTTPName

Default: `Not Found`.

**INI**

```
<?php /* #?ini charset="utf-8"?
# settings/override/error.ini.append.php
[HTTPError-404]
HTTPName=Not Found
*/ ?>
```

## HeaderList

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/error.ini.append.php
[HTTPError-404]
# an empty "HeaderList[]" first replaces the shipped list; without it the items are added
HeaderList[]
*/ ?>
```

## Related

- All blocks of error.ini
- All INI files
- The settings page

---

Generated by `./console exp:help:examples` from `settings/error.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

---

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.