httpcache.ini

The blocks and settings of httpcache.ini.

Source file: `doc/eng-us/examples/ini-settings/httpcache/README.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/httpcache/README.md

The shipped settings of `settings/httpcache.ini`: 1 blocks, 9 settings.

> The role-aware HTTP cache: rendered content views kept per permission context and served before the kernel boots (config.php early exit) or from Exponential Velocity's parent. Off by default; see kernel/private/classes/httpcache/.

Block	Settings
HttpCacheSettings	9

- All examples

Generated by `./console exp:help:examples` from `settings/httpcache.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.