kernelservices.ini [Service_http]

The settings of [Service_http] in kernelservices.ini: Class, Factory, Scope, Tags, Description

Source file: doc/eng-us/examples/ini-settings/kernelservices/Service_http.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/kernelservices/Service_http.md

The block `[Service_http]` of `settings/kernelservices.ini`, with 5 setting(s).

Never edit `settings/kernelservices.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/kernelservices.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/kernelservices.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/kernelservices.ini.append.php` in an extension (read when the extension is active).

Class

Default: `eZHTTPTool`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_http]
Class=eZHTTPTool
*/ ?>
```

Factory

Default: `eZHTTPTool::instance`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_http]
Factory=eZHTTPTool::instance
*/ ?>
```

Scope

Default: `request`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_http]
Scope=request
*/ ?>
```

Tags

Default: a list of 1: `kernel.core`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_http]
# an empty "Tags[]" first replaces the shipped list; without it the items are added
Tags[]
Tags[]=kernel.core
*/ ?>
```

Description

Default: `The HTTP request helper (eZHTTPTool::instance()).`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_http]
Description=The HTTP request helper (eZHTTPTool::instance()).
*/ ?>
```

Related

- All blocks of kernelservices.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/kernelservices.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.