kernelservices.ini [Service_transfer.rss_export]

The settings of [Service_transfer.rss_export] in kernelservices.ini: Class, Factory, Arguments, Scope, Tags, Description, Name, Direction ...

Source file: `doc/eng-us/examples/ini-settings/kernelservices/Service_transfer.rss_export.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/kernelservices/Service_transfer.rss_export.md

The block `[Service_transfer.rss_export]` of `settings/kernelservices.ini`, with 16 setting(s).

Never edit `settings/kernelservices.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/kernelservices.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/kernelservices.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/kernelservices.ini.append.php` in an extension (read when the extension is active).

Class

Default: `expKernelTransferTool`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Class=expKernelTransferTool
*/ ?>
```

Factory

Default: `expKernelTransferTool::fromSettings`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Factory=expKernelTransferTool::fromSettings
*/ ?>
```

Arguments

Default: a list of 1: `transfer.rss_export`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "Arguments[]" first replaces the shipped list; without it the items are added
Arguments[]
Arguments[]=transfer.rss_export
*/ ?>
```

Scope

Default: `worker`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Scope=worker
*/ ?>
```

Tags

Default: a list of 1: `transfer.tool`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "Tags[]" first replaces the shipped list; without it the items are added
Tags[]
Tags[]=transfer.tool
*/ ?>
```

Description

Default: `Publish the newest items of a folder as an RSS or Atom feed, or a list of feeds as OPML.`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Description=Publish the newest items of a folder as an RSS or Atom feed, or a list of feeds as OP
ML.
*/ ?>
```

Name

Default: `RSS export`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Name=RSS export
*/ ?>
```

Direction

Default: `export`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Direction=export
*/ ?>
```

Scopes

Default: a list of 1: `subtree`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "Scopes[]" first replaces the shipped list; without it the items are added
Scopes[]
Scopes[]=subtree
*/ ?>
```

Formats

Default: a list of 3: `RSS`, `Atom`, `OPML`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "Formats[]" first replaces the shipped list; without it the items are added
Formats[]
Formats[]=RSS
Formats[]=Atom
Formats[]=OPML
*/ ?>
```

EntryURL

Default: `rss/list`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
EntryURL=rss/list
*/ ?>
```

Permission

Default: `rss/edit`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Permission=rss/edit
*/ ?>
```

HelpPage

Default: `guides/rss-feeds.md#3-an-export-card`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
HelpPage=guides/rss-feeds.md#3-an-export-card
*/ ?>
```

RoundTrip

Default: a list of 1: `transfer.rss_import`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "RoundTrip[]" first replaces the shipped list; without it the items are added
RoundTrip[]
RoundTrip[]=transfer.rss_import
*/ ?>
```

Keywords

Default: a list of 4: `feed`, `newsletter feed`, `subscribe`, `abonnieren`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
# an empty "Keywords[]" first replaces the shipped list; without it the items are added
Keywords[]
Keywords[]=feed
Keywords[]=newsletter feed
Keywords[]=subscribe
Keywords[]=abonnieren
*/ ?>
```

Weight

Default: `61`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/kernelservices.ini.append.php
[Service_transfer.rss_export]
Weight=61
*/ ?>
```

Related

- All blocks of kernelservices.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/kernelservices.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.