menu.ini [Leftmenu_setup]

The settings of [Leftmenu_setup] in menu.ini: Name, Groups, GroupNames, GroupTabs, GroupTabsLeftMenu, GroupSections, GroupLinks_content_model, GroupLinks_site ...

Source file: doc/eng-us/examples/ini-settings/menu/Leftmenu_setup.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/menu/Leftmenu_setup.md

The block `[Leftmenu_setup]` of `settings/menu.ini`, with 68 setting(s).

Never edit `settings/menu.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/menu.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/menu.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/menu.ini.append.php` in an extension (read when the extension is active).

Name

Default: `setup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
Name=setup
*/ ?>
```

Groups

> Groups of the left menu (admin4, parts/ini_menu.tpl): Groups[] in their order,
> GroupNames[<group>] the title,
> GroupLinks_<group>[] the link keys. Links in no group follow under "More", the last group.
> For one plain list
> reset Groups[] (a line Groups[] with no values) in an override. Only the arrangement
> changes: access is checked per
> link as before.
> The groups ai and updates hold the links of extensions: a key listed there whose extension
> is not active shows
> nothing, and a group without a link the user may open is not drawn. An extension puts its
> own link in a group with
> GroupLinks_<group>[]=<key> in its menu.ini.append.php
> (doc/eng-us/features/6.0/admin4-design.md, "Setup overview").

Default: a list of 10: `content_model`, `site`, `design`, `workflow`, `users`, `audit`, `data`, `system`, `ai`, `updates`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "Groups[]" first replaces the shipped list; without it the items are added
Groups[]
Groups[]=content_model
Groups[]=site
Groups[]=design
Groups[]=workflow
Groups[]=users
Groups[]=audit
Groups[]=data
Groups[]=system
Groups[]=ai
Groups[]=updates
*/ ?>
```

GroupNames

Default: a hash of 10: `content_model=Content model`, `site=Site and URLs`, `design=Design`, `workflow=Workflows`, `users=Users and messages`, `audit=Audit`, `data=Data tables`, `system=System`, `ai=AI`, `updates=Updates`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupNames[]" first replaces the shipped list; without it the items are added
GroupNames[]
GroupNames[content_model]=Content model
GroupNames[site]=Site and URLs
GroupNames[design]=Design
GroupNames[workflow]=Workflows
GroupNames[users]=Users and messages
GroupNames[audit]=Audit
GroupNames[data]=Data tables
GroupNames[system]=System
GroupNames[ai]=AI
GroupNames[updates]=Updates
*/ ?>
```

GroupTabs

> A group that stands for a top tab (admin4): GroupTabs[<group>]=<tab> shows the group only while the tab is not in
> the top menu (left out of [TopAdminMenu] Tabs[], named in HiddenTabs[], or named in SetupTabs[] for a user who
> may open setup/menu); then the tab's pages (its
> NavigationPartIdentifier) mark the Setup tab and draw this menu. While the tab is shown, the group and its links
> are not here at all. GroupSections[<group>]=<section> adds the links of another left menu to the group, after its
> GroupLinks_<group>[]: that section's Links[], names, PolicyList[] and PolicyList_<key>[], Enabled_<key>[] and tile

> settings (LinkIcons[], LinkDescriptions[], LinkFigureTemplates[]), so the tab's menu and the group stay one list.
> A Setup link to an address the added menu has too shows in that group only.

Default: a hash of 2: `design=design`, `audit=audit`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupTabs[]" first replaces the shipped list; without it the items are added
GroupTabs[]
GroupTabs[design]=design
GroupTabs[audit]=audit
*/ ?>
```

GroupTabsLeftMenu

> The left menu of the pages of such a tab while it is moved into Setup (admin4 page_leftmenu.tpl, admin4l's left menu
> block): setup draws this menu with the tab's group open (default); tab draws the tab's own left menu (the view's
> left_menu, else parts/<part>/menu.tpl), while the top menu still marks the Setup tab and opens the Setup mega menu;
> the path above the page is the view's own either way. design/admin and exp_adminui never move a tab into Setup, so they always draw the tab's own menu (doc/eng-us/features/6.0/admin4-design.md, "Moving a tab into Setup").

Default: `setup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
GroupTabsLeftMenu=setup
*/ ?>
```

GroupSections

Default: a hash of 2: `design=Leftmenu_design`, `audit=Leftmenu_audit`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupSections[]" first replaces the shipped list; without it the items are added
GroupSections[]
GroupSections[design]=Leftmenu_design
GroupSections[audit]=Leftmenu_audit
*/ ?>
```

GroupLinks_content_model

Default: a list of 11: `classes`, `datatypes`, `sections`, `states`, `languages`, `interface_languages`, `contentfinder`, `unreferenced_objects`, `broken_relations`, `storage_files`, `collected`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_content_model[]" first replaces the shipped list; without it the items are
 added
GroupLinks_content_model[]
GroupLinks_content_model[]=classes
GroupLinks_content_model[]=datatypes
GroupLinks_content_model[]=sections
GroupLinks_content_model[]=states
GroupLinks_content_model[]=languages
GroupLinks_content_model[]=interface_languages
GroupLinks_content_model[]=contentfinder
GroupLinks_content_model[]=unreferenced_objects
GroupLinks_content_model[]=broken_relations
GroupLinks_content_model[]=storage_files
GroupLinks_content_model[]=collected
*/ ?>
```

GroupLinks_site

Default: a list of 9: `preload`, `rss`, `packages`, `pdf_export`, `search_statistics`, `url_management`, `url_translator`, `url_wildcards`, `rad`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_site[]" first replaces the shipped list; without it the items are added
GroupLinks_site[]
GroupLinks_site[]=preload
GroupLinks_site[]=rss
GroupLinks_site[]=packages
GroupLinks_site[]=pdf_export
GroupLinks_site[]=search_statistics
GroupLinks_site[]=url_management
GroupLinks_site[]=url_translator
GroupLinks_site[]=url_wildcards
GroupLinks_site[]=rad
*/ ?>
```

GroupLinks_design

Default: a list of 1: `design_node`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_design[]" first replaces the shipped list; without it the items are added
GroupLinks_design[]
GroupLinks_design[]=design_node
*/ ?>
```

GroupLinks_workflow

Default: a list of 3: `workflows`, `workflow_processes`, `triggers`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_workflow[]" first replaces the shipped list; without it the items are adde
d
GroupLinks_workflow[]
GroupLinks_workflow[]=workflows
GroupLinks_workflow[]=workflow_processes
GroupLinks_workflow[]=triggers
*/ ?>
```

GroupLinks_users

Default: a list of 6: `user_hygiene`, `sessions`, `notification`, `mailpreferences`, `oauth_list`, `audit`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_users[]" first replaces the shipped list; without it the items are added
GroupLinks_users[]
GroupLinks_users[]=user_hygiene
GroupLinks_users[]=sessions
GroupLinks_users[]=notification
GroupLinks_users[]=mailpreferences
GroupLinks_users[]=oauth_list
GroupLinks_users[]=audit
*/ ?>
```

GroupLinks_data

Default: a list of 5: `datatables`, `data_connections`, `secrets`, `graphql`, `data_syncs`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_data[]" first replaces the shipped list; without it the items are added
GroupLinks_data[]
GroupLinks_data[]=datatables
GroupLinks_data[]=data_connections
GroupLinks_data[]=secrets
GroupLinks_data[]=graphql
GroupLinks_data[]=data_syncs
*/ ?>
```

GroupLinks_system

> extensions: expqueue (the job queue, also shipped with expai), sevenx_dse (the database editor)

Default: a list of 14: `cache`, `static_publishing`, `system_information`, `help_center`, `upgrade_check`, `migrations`, `maintenance`, `cronjobs`, `logs`, `extensions`, `ini`, `sitedata` ….

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_system[]" first replaces the shipped list; without it the items are added
GroupLinks_system[]
GroupLinks_system[]=cache
GroupLinks_system[]=static_publishing
GroupLinks_system[]=system_information
GroupLinks_system[]=help_center
GroupLinks_system[]=upgrade_check
GroupLinks_system[]=migrations
GroupLinks_system[]=maintenance
GroupLinks_system[]=cronjobs
GroupLinks_system[]=logs
GroupLinks_system[]=extensions
GroupLinks_system[]=ini
GroupLinks_system[]=sitedata
GroupLinks_system[]=expqueue
GroupLinks_system[]=dse
*/ ?>
```

GroupLinks_ai

> extensions: expai

Default: a list of 3: `expai_summary`, `expai_models`, `expai_budgets`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_ai[]" first replaces the shipped list; without it the items are added
GroupLinks_ai[]
GroupLinks_ai[]=expai_summary
GroupLinks_ai[]=expai_models
GroupLinks_ai[]=expai_budgets
*/ ?>
```

GroupLinks_updates

> extensions: ezupdate, git_manager

Default: a list of 3: `ezupdate`, `git_manager`, `git_manager_backup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "GroupLinks_updates[]" first replaces the shipped list; without it the items are added
GroupLinks_updates[]
GroupLinks_updates[]=ezupdate
GroupLinks_updates[]=git_manager
GroupLinks_updates[]=git_manager_backup
*/ ?>
```

LeadLinks

> Links shown before the groups and in none of them: the overview (setup/menu), every link of this menu as a tile
> in the same groups. An extension's link in no group shows under "More" in the menu and on the overview.

Default: a list of 1: `overview`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "LeadLinks[]" first replaces the shipped list; without it the items are added
LeadLinks[]
LeadLinks[]=overview
*/ ?>
```

MegaMenuLinks

> admin4's mega menu (prototype, [TopAdminMenu] MegaMenuTabs[]=setup): the links of this menu it shows, by link key,
> in this order; at most 19 (6 to 19 read best), the rest is one click away under "Go to Setup" (the overview).

> Each link keeps its group (GroupNames[]) and its access checks: a link the user may not open, or whose extension is not
> active, is left out, and so is a group with no link left. The groups follow the order of their first link here.
> A list reset to no values shows every link of the menu, as the overview does.
> Log files (setup/logs) took the place of Link management (url/list), which stays one click away in the
> group "Site and URLs" of the overview. Collected information (Content model) and RSS (Site and URLs) were added
> in 6.0.15, and so were Preload sites and Packages (Site and URLs) and EI: Models and EI: Budgets (AI) and oAuth admin
> (Users and messages): the list holds nineteen.

Default: a list of 19: `classes`, `sections`, `collected`, `rss`, `preload`, `packages`, `audit`, `oauth_list`, `cache`, `cronjobs`, `logs`, `extensions` ....

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "MegaMenuLinks[]" first replaces the shipped list; without it the items are added
MegaMenuLinks[]
MegaMenuLinks[]=classes
MegaMenuLinks[]=sections
MegaMenuLinks[]=collected
MegaMenuLinks[]=rss
MegaMenuLinks[]=preload
MegaMenuLinks[]=packages
MegaMenuLinks[]=audit
MegaMenuLinks[]=oauth_list
MegaMenuLinks[]=cache
MegaMenuLinks[]=cronjobs
MegaMenuLinks[]=logs
MegaMenuLinks[]=extensions
MegaMenuLinks[]=system_information
MegaMenuLinks[]=ini
MegaMenuLinks[]=expai_summary
MegaMenuLinks[]=expai_models
MegaMenuLinks[]=expai_budgets
MegaMenuLinks[]=ezupdate
MegaMenuLinks[]=git_manager
*/ ?>
```

LinkIcons

> The Setup overview (setup/menu) draws this menu as tiles. Per link key, all optional:
> LinkIcons[<key>]=<icon> an icon of design.ini [AdminDesignSettings] IconList[] (a Bootstrap icon name,
> e.g. bar-chart); a name not listed there, or no entry, draws the plug icon
> LinkDescriptions[<key>]=<text> one line on what the function does, translated in the menu's context
> (design/admin/parts/setup/menu) like LinkNames[]
> LinkFigureTemplates[<key>]=design:<path>.tpl a template that draws the tile's figure, included with

> figure_key=<key> for a shown tile only; empty or not design: draws none
> An extension sets them for its own link in its menu.ini.append.php
> (doc/eng-us/features/6.0/admin4-design.md).

Default: a hash of 61: `audit=journal-check`, `broken_relations=exclamation-diamond`, `storage_files=files`, `cache=arrow-clockwise`, `classes=diagram-3`, `datatypes=ui-radios`, `collected=inbox`, `contentfinder=search`, `cronjobs=clock`, `design_node=brush`, `dse=database`, `expai_budgets=piggy-bank` ….

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "LinkIcons[]" first replaces the shipped list; without it the items are added
LinkIcons[]
LinkIcons[audit]=journal-check
LinkIcons[broken_relations]=exclamation-diamond
LinkIcons[storage_files]=files
LinkIcons[cache]=arrow-clockwise
LinkIcons[classes]=diagram-3
LinkIcons[datatypes]=ui-radios
LinkIcons[collected]=inbox
LinkIcons[contentfinder]=search
LinkIcons[cronjobs]=clock
LinkIcons[design_node]=brush
LinkIcons[dse]=database
LinkIcons[expai_budgets]=piggy-bank
LinkIcons[expai_models]=cpu
LinkIcons[expai_summary]=stars
LinkIcons[expqueue]=list-task
LinkIcons[extensions]=puzzle
LinkIcons[ezupdate]=cloud-arrow-down
LinkIcons[git_manager]=git
LinkIcons[git_manager_backup]=archive
LinkIcons[global_setting]=globe
# ... 41 more in the shipped file
*/ ?>
```

LinkDescriptions

Default: a hash of 61: `audit=Who changed what: the audit settings and archives.`, `broken_relations=Visible content that links to deleted, hidden or trashed content.`, `storage_files=Files in the storage that nothing uses, and files with the wrong owner or mode.`, `cache=Clear or regenerate the caches.`, `classes=The content classes and their attributes.`, `datatypes=Every datatype of the kernel and the extensions, and how the classes and content use it.`, `collected=What visitors sent through forms.`, `contentfinder=Find content by its id, remote id or path.`, `cronjobs=The cronjob parts, their scripts and last runs.`, `design_node=The design's top node and the objects below it.`, `dse=Browse and query the database directly.`, `expai_budgets=AI budgets, queued requests and what they cost.` ….

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "LinkDescriptions[]" first replaces the shipped list; without it the items are added
```

```
LinkDescriptions[]
LinkDescriptions[audit]=Who changed what: the audit settings and archives.
LinkDescriptions[broken_relations]=Visible content that links to deleted, hidden or trashed conte
nt.
LinkDescriptions[storage_files]=Files in the storage that nothing uses, and files with the wrong
owner or mode.
LinkDescriptions[cache]=Clear or regenerate the caches.
LinkDescriptions[classes]=The content classes and their attributes.
LinkDescriptions[datatypes]=Every datatype of the kernel and the extensions, and how the classes
and content use it.
LinkDescriptions[collected]=What visitors sent through forms.
LinkDescriptions[contentfinder]=Find content by its id, remote id or path.
LinkDescriptions[cronjobs]=The cronjob parts, their scripts and last runs.
LinkDescriptions[design_node]=The design's top node and the objects below it.
LinkDescriptions[dse]=Browse and query the database directly.
LinkDescriptions[expai_budgets]=AI budgets, queued requests and what they cost.
LinkDescriptions[expai_models]=The AI providers and models, and their tests.
LinkDescriptions[expai_summary]=What the AI features send where, on one printable page.
LinkDescriptions[expqueue]=Background jobs: waiting, running and failed.
LinkDescriptions[extensions]=Activate and deactivate extensions.
LinkDescriptions[ezupdate]=Packages with a newer release, and their updates.
LinkDescriptions[git_manager]=The Git checkout of the installation and its updates.
LinkDescriptions[git_manager_backup]=Make, download and remove backups.
LinkDescriptions[global_setting]=The settings of the whole site.
# ... 41 more in the shipped file
*/ ?>
```

LinkFigureTemplates

Default: a hash of 6: `classes=design:setup/setupmenu_figure.tpl`, `sections=design:setup/setupmenu_figure.tpl`, `languages=design:setup/setupmenu_figure.tpl`, `extensions=design:setup/setupmenu_figure.tpl`, `sessions=design:setup/setupmenu_figure.tpl`, `cronjobs=design:setup/setupmenu_figure.tpl`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "LinkFigureTemplates[]" first replaces the shipped list; without it the items are adde
d
LinkFigureTemplates[]
LinkFigureTemplates[classes]=design:setup/setupmenu_figure.tpl
LinkFigureTemplates[sections]=design:setup/setupmenu_figure.tpl
LinkFigureTemplates[languages]=design:setup/setupmenu_figure.tpl
LinkFigureTemplates[extensions]=design:setup/setupmenu_figure.tpl
LinkFigureTemplates[sessions]=design:setup/setupmenu_figure.tpl
LinkFigureTemplates[cronjobs]=design:setup/setupmenu_figure.tpl
*/ ?>
```

Links

> No PolicyList_overview[]: the view opens with any one of the setup module's functions (kernel/setup/module.php),
> which one PolicyList entry cannot say; CheckViewAccess asks the view itself.
> Static publishing (module staticpublish): a site published as static files to GitHub Pages or

any git host
(doc/eng-us/help/static-publishing/README.md)
The audit settings and archives (doc/eng-us/bc/6.0/audit.md, "Placement"), only with audit/manage
The datatypes (class/datatype): every registered datatype, its provider and how the content model uses it
The content finder (doc/eng-us/features/6.0/content-finder.md): find content by id or path, only with contentfinder/search
The content checks (doc/eng-us/features/6.0/content-checks.md): unreferenced objects and broken relations, each only
with its policy
The cronjobs console. LinkNames is what the entry reads as: without it the
menu falls back to the key, and "cronjobs" is not a label.
Migrations (module migration): the migrations of the site and its extensions, their runs, a run or a rollback in
the background, the log of each run
The log viewer (doc/eng-us/features/6.0/log-viewer.md): follow, search and cross-reference the log files, only with setup/logs
The Design tab's page (its URL[default]), in the group that stands for the tab (GroupTabs[design]): shown only
while the tab is not in the top menu
Removed from 4.3. Enable if you have special requirements.
Links[global_setting]=content/edit/52
PolicyList_global_setting[]=54
The translation fallbacks of every interface language (doc/eng-us/languages.md), read only
The e-mail preferences for administrators: status, categories, suppression list, consent log
Removed from 4.3. Enable if you have special requirements.
Links[look_and_feel]=content/edit/54
PolicyList_look_and_feel[]=56
The menus of the classic site designs (visual/menuconfig) are a link of the Design menu ([Leftmenu_design])
The notification status (pending events, digest messages, the last runs of the notification cronjob, problems)
Preload Sites, RSS and Packages open the group "Site and URLs" (GroupLinks_site[]), RAD closes it: a group draws its
links in the order of Links[], so their order here is the order of the group
Disabled by default in 4.3 as it is also present in user account tab.
Links[roles_and_policies]=role/list
PolicyList_roles_and_policies[]=role/*
Check user accounts (doc/eng-us/features/6.0/user-hygiene.md): never signed in, not seen for long, disabled, locked,
orphaned, a shared e-mail address; only with user/hygiene. The same key is in [Leftmenu_user].
The data tables, the named database connections and the secret store (doc/eng-us/features/6.0/data-tables.md,
doc/eng-us/features/6.0/secret-store.md)
The GraphQL API (doc/eng-us/features/6.0/graphql.md)
The rows of ezsite_data, read only (Setup > Site data)
The Help center, the start page of the help (exphelp/dashboard)

> Removed from 4.3. Enable if you have special requirements.
> Links[templates]=visual/templatelist
> PolicyList_templates[]=visual/*
> Removed from 4.3. Enable if you have special requirements.
> Links[toolbar_management]=visual/toolbarlist
> PolicyList_toolbar_management[]=visual/*
> RAD closes the group "Site and URLs"

Default: a hash of 48: `overview=setup/menu`, `cache=setup/cache`, `static_publishing=staticpublish/dashboard`, `audit=audit/settings`, `classes=class/grouplist`, `datatypes=class/datatype/list`, `collected=infocollector/overview`, `contentfinder=contentfinder/search`, `unreferenced_objects=contentcheck/unreferenced`, `broken_relations=contentcheck/brokenrelations`, `storage_files=contentcheck/storage`, `maintenance=setup/maintenance` ....

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "Links[]" first replaces the shipped list; without it the items are added
Links[]
Links[overview]=setup/menu
Links[cache]=setup/cache
Links[static_publishing]=staticpublish/dashboard
Links[audit]=audit/settings
Links[classes]=class/grouplist
Links[datatypes]=class/datatype/list
Links[collected]=infocollector/overview
Links[contentfinder]=contentfinder/search
Links[unreferenced_objects]=contentcheck/unreferenced
Links[broken_relations]=contentcheck/brokenrelations
Links[storage_files]=contentcheck/storage
Links[maintenance]=setup/maintenance
Links[migrations]=migration/status
Links[cronjobs]=setup/cronjobs
Links[logs]=setup/logs
Links[extensions]=setup/extensions
Links[design_node]=content/view/full/58
Links[ini]=settings/view
Links[languages]=content/translations
Links[interface_languages]=setup/languages
# ... 28 more in the shipped file
*/ ?>
```

LinkNames

Default: a hash of 22: `static_publishing=Static publishing`, `audit=Audit`, `datatypes=Datatypes`, `contentfinder=Content finder`, `unreferenced_objects=Unreferenced objects`, `broken_relations=Broken relations`, `storage_files=Storage files`, `maintenance=Maintenance`, `migrations=Migrations`, `cronjobs=Cronjobs`, `logs=Log files`, `design_node=Design content` ....

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "LinkNames[]" first replaces the shipped list; without it the items are added
LinkNames[]
LinkNames[static_publishing]=Static publishing
LinkNames[audit]=Audit
LinkNames[datatypes]=Datatypes
LinkNames[contentfinder]=Content finder
LinkNames[unreferenced_objects]=Unreferenced objects
LinkNames[broken_relations]=Broken relations
LinkNames[storage_files]=Storage files
LinkNames[maintenance]=Maintenance
LinkNames[migrations]=Migrations
LinkNames[cronjobs]=Cronjobs
LinkNames[logs]=Log files
LinkNames[design_node]=Design content
LinkNames[interface_languages]=Interface languages
LinkNames[preload]=Preload Sites
LinkNames[user_hygiene]=Check user accounts
LinkNames[datatables]=Data tables
LinkNames[data_connections]=Connections
LinkNames[secrets]=Secrets
LinkNames[graphql]=GraphQL
LinkNames[data_syncs]=Synchronisations
# ... 2 more in the shipped file
*/ ?>
```

PolicyList_cache

Default: a list of 1: `setup/managecache`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_cache[]" first replaces the shipped list; without it the items are added
PolicyList_cache[]
PolicyList_cache[]=setup/managecache
*/ ?>
```

PolicyList_static_publishing

Default: a list of 1: `staticpublish/read`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_static_publishing[]" first replaces the shipped list; without it the items
 are added
PolicyList_static_publishing[]
PolicyList_static_publishing[]=staticpublish/read
*/ ?>
```

PolicyList_audit

Default: a list of 1: `audit/manage`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_audit[]" first replaces the shipped list; without it the items are added
PolicyList_audit[]
PolicyList_audit[]=audit/manage
*/ ?>
```

PolicyList_classes

Default: a list of 1: `class/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_classes[]" first replaces the shipped list; without it the items are added
PolicyList_classes[]
PolicyList_classes[]=class/*
*/ ?>
```

PolicyList_datatypes

Default: a list of 1: `class/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_datatypes[]" first replaces the shipped list; without it the items are add
ed
PolicyList_datatypes[]
PolicyList_datatypes[]=class/*
*/ ?>
```

PolicyList_collected

Default: a list of 1: `infocollector/read`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_collected[]" first replaces the shipped list; without it the items are add
ed
PolicyList_collected[]
PolicyList_collected[]=infocollector/read
*/ ?>
```

PolicyList_contentfinder

Default: a list of 1: `contentfinder/search`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_contentfinder[]" first replaces the shipped list; without it the items are
 added
PolicyList_contentfinder[]
PolicyList_contentfinder[]=contentfinder/search
*/ ?>
```

PolicyList_unreferenced_objects

Default: a list of 1: `contentcheck/unreferenced`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_unreferenced_objects[]" first replaces the shipped list; without it the it
ems are added
PolicyList_unreferenced_objects[]
PolicyList_unreferenced_objects[]=contentcheck/unreferenced
*/ ?>
```

PolicyList_broken_relations

Default: a list of 1: `contentcheck/brokenrelations`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_broken_relations[]" first replaces the shipped list; without it the items
are added
PolicyList_broken_relations[]
PolicyList_broken_relations[]=contentcheck/brokenrelations
*/ ?>
```

PolicyList_storage_files

Default: a list of 1: `contentcheck/storage`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_storage_files[]" first replaces the shipped list; without it the items are
 added
PolicyList_storage_files[]
PolicyList_storage_files[]=contentcheck/storage
*/ ?>
```

PolicyList_maintenance

Default: a list of 1: `setup/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_maintenance[]" first replaces the shipped list; without it the items are a
dded
PolicyList_maintenance[]
PolicyList_maintenance[]=setup/administrate
*/ ?>
```

PolicyList_migrations

Default: a list of 1: `migration/read`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_migrations[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_migrations[]
PolicyList_migrations[]=migration/read
*/ ?>
```

PolicyList_cronjobs

Default: a list of 1: `setup/managecronjobs`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_cronjobs[]" first replaces the shipped list; without it the items are adde
d
PolicyList_cronjobs[]
PolicyList_cronjobs[]=setup/managecronjobs
*/ ?>
```

PolicyList_logs

Default: a list of 1: `setup/logs`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_logs[]" first replaces the shipped list; without it the items are added
PolicyList_logs[]
PolicyList_logs[]=setup/logs
*/ ?>
```

PolicyList_extensions

Default: a list of 1: `setup/setup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_extensions[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_extensions[]
PolicyList_extensions[]=setup/setup
*/ ?>
```

PolicyList_design_node

Default: a list of 1: `58`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_design_node[]" first replaces the shipped list; without it the items are a
dded
PolicyList_design_node[]
PolicyList_design_node[]=58
*/ ?>
```

PolicyList_ini

Default: a list of 1: `settings/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_ini[]" first replaces the shipped list; without it the items are added
PolicyList_ini[]
PolicyList_ini[]=settings/*
*/ ?>
```

PolicyList_languages

Default: a list of 1: `content/translations`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_languages[]" first replaces the shipped list; without it the items are add
ed
PolicyList_languages[]
PolicyList_languages[]=content/translations
*/ ?>
```

PolicyList_interface_languages

Default: a list of 1: `setup/system_info`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_interface_languages[]" first replaces the shipped list; without it the ite
ms are added
PolicyList_interface_languages[]
PolicyList_interface_languages[]=setup/system_info
*/ ?>
```

PolicyList_mailpreferences

Default: a list of 1: `mailpreferences/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_mailpreferences[]" first replaces the shipped list; without it the items a
re added
PolicyList_mailpreferences[]
PolicyList_mailpreferences[]=mailpreferences/administrate
*/ ?>
```

PolicyList_notification

Default: a list of 1: `notification/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_notification[]" first replaces the shipped list; without it the items are
added
PolicyList_notification[]
PolicyList_notification[]=notification/administrate
*/ ?>
```

PolicyList_preload

Default: a list of 1: `setup/preload`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_preload[]" first replaces the shipped list; without it the items are added
PolicyList_preload[]
PolicyList_preload[]=setup/preload
*/ ?>
```

PolicyList_rss

Default: a list of 1: `rss/edit`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_rss[]" first replaces the shipped list; without it the items are added
PolicyList_rss[]
PolicyList_rss[]=rss/edit
*/ ?>
```

PolicyList_packages

Default: a list of 1: `package/list`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_packages[]" first replaces the shipped list; without it the items are adde
d
PolicyList_packages[]
PolicyList_packages[]=package/list
*/ ?>
```

PolicyList_pdf_export

Default: a list of 1: `pdf/edit`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_pdf_export[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_pdf_export[]
PolicyList_pdf_export[]=pdf/edit
*/ ?>
```

PolicyList_search_statistics

Default: a list of 1: `search/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_search_statistics[]" first replaces the shipped list; without it the items
 are added
PolicyList_search_statistics[]
PolicyList_search_statistics[]=search/*
*/ ?>
```

PolicyList_sessions

Default: a list of 1: `setup/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_sessions[]" first replaces the shipped list; without it the items are adde
d
PolicyList_sessions[]
PolicyList_sessions[]=setup/administrate
*/ ?>
```

PolicyList_user_hygiene

Default: a list of 1: `user/hygiene`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_user_hygiene[]" first replaces the shipped list; without it the items are
added
PolicyList_user_hygiene[]
PolicyList_user_hygiene[]=user/hygiene
*/ ?>
```

PolicyList_datatables

Default: a list of 1: `datatable/read`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_datatables[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_datatables[]
PolicyList_datatables[]=datatable/read
*/ ?>
```

PolicyList_data_connections

Default: a list of 1: `datatable/connections`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_data_connections[]" first replaces the shipped list; without it the items
are added
PolicyList_data_connections[]
PolicyList_data_connections[]=datatable/connections
*/ ?>
```

PolicyList_secrets

Default: a list of 1: `secrets/manage`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_secrets[]" first replaces the shipped list; without it the items are added
PolicyList_secrets[]
PolicyList_secrets[]=secrets/manage
*/ ?>
```

PolicyList_graphql

Default: a list of 1: `graphql/playground`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_graphql[]" first replaces the shipped list; without it the items are added
PolicyList_graphql[]
PolicyList_graphql[]=graphql/playground
*/ ?>
```

PolicyList_data_syncs

Default: a list of 1: `datatable/sync`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_data_syncs[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_data_syncs[]
PolicyList_data_syncs[]=datatable/sync
*/ ?>
```

PolicyList_sitedata

Default: a list of 1: `setup/system_info`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_sitedata[]" first replaces the shipped list; without it the items are adde
d
PolicyList_sitedata[]
PolicyList_sitedata[]=setup/system_info
*/ ?>
```

PolicyList_states

Default: a list of 1: `state/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_states[]" first replaces the shipped list; without it the items are added
PolicyList_states[]
PolicyList_states[]=state/administrate
*/ ?>
```

PolicyList_system_information

Default: a list of 1: `setup/system_info`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_system_information[]" first replaces the shipped list; without it the item
s are added
PolicyList_system_information[]
PolicyList_system_information[]=setup/system_info
*/ ?>
```

PolicyList_help_center

Default: a list of 1: `exphelp/read`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_help_center[]" first replaces the shipped list; without it the items are a
dded
PolicyList_help_center[]
PolicyList_help_center[]=exphelp/read
*/ ?>
```

PolicyList_upgrade_check

Default: a list of 1: `setup/setup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_upgrade_check[]" first replaces the shipped list; without it the items are
 added
PolicyList_upgrade_check[]
PolicyList_upgrade_check[]=setup/setup
*/ ?>
```

PolicyList_triggers

Default: a list of 1: `trigger/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_triggers[]" first replaces the shipped list; without it the items are adde
d
PolicyList_triggers[]
PolicyList_triggers[]=trigger/*
*/ ?>
```

PolicyList_url_management

Default: a list of 1: `url/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_url_management[]" first replaces the shipped list; without it the items ar
e added
PolicyList_url_management[]
PolicyList_url_management[]=url/*
*/ ?>
```

PolicyList_url_translator

Default: a list of 1: `content/urltranslator`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_url_translator[]" first replaces the shipped list; without it the items ar
e added
PolicyList_url_translator[]
PolicyList_url_translator[]=content/urltranslator
*/ ?>
```

PolicyList_url_wildcards

Default: a list of 1: `content/urltranslator`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_url_wildcards[]" first replaces the shipped list; without it the items are
 added
PolicyList_url_wildcards[]
PolicyList_url_wildcards[]=content/urltranslator
*/ ?>
```

PolicyList_rad

Default: a list of 1: `setup/setup`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_rad[]" first replaces the shipped list; without it the items are added
PolicyList_rad[]
PolicyList_rad[]=setup/setup
*/ ?>
```

PolicyList_workflows

Default: a list of 1: `workflow/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_workflows[]" first replaces the shipped list; without it the items are add
ed
PolicyList_workflows[]
PolicyList_workflows[]=workflow/*
*/ ?>
```

PolicyList_workflow_processes

Default: a list of 1: `workflow/*`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_workflow_processes[]" first replaces the shipped list; without it the item
s are added
PolicyList_workflow_processes[]
PolicyList_workflow_processes[]=workflow/*
*/ ?>
```

PolicyList_oauth_list

> The views of oauthadmin define no policy functions: the module's own access (oauthadmin/*), as the kernel checks it

Default: a list of 1: `oauthadmin/*`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_setup]
# an empty "PolicyList_oauth_list[]" first replaces the shipped list; without it the items are ad
ded
PolicyList_oauth_list[]
PolicyList_oauth_list[]=oauthadmin/*
*/ ?>
```

Related

- All blocks of menu.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/menu.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.