menu.ini [Leftmenu_user_mega]

The settings of [Leftmenu_user_mega] in menu.ini: Name, Links, LinkNames, PolicyList_accounts, PolicyList_sessions, Groups, GroupNames, GroupLinks_users ...

Source file: `doc/eng-us/examples/ini-settings/menu/Leftmenu_user_mega.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/menu/Leftmenu_user_mega.md

The block `[Leftmenu_user_mega]` of `settings/menu.ini`, with 12 setting(s).

> admin4's mega menu of the Users tab ([TopAdminMenu] MegaMenuTabs[]=users, [Topmenu_users] MegaMenuTemplate,
> drawn by parts/user/mega_menu.tpl through parts/ini_menu.tpl). Not a left menu: the Users tab's left menu is the
> user tree and [Leftmenu_user] (parts/user/menu.tpl), and a tree is no list of links. This section only gathers
> the tab's functions in groups, and it reuses the menus that already define them instead of restating them:
> GroupSections[] adds [Leftmenu_user] (Roles and policies, Unactivated users) and [Leftmenu_my] (the user's own
> settings) with their addresses, policies, icons and descriptions; its own links are the two the Users tab has no
> menu entry for, the user tree and the sessions. Named Leftmenu_user_* so that it shares the translation context
> of the tab's menu, design/admin/parts/user/menu. MegaMenuLinks[] chooses from all of them, a link of an added
> section as <group>-<key>; at most 12 are shown, each in its group and only when the user may open it.

Never edit `settings/menu.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/menu.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/menu.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/menu.ini.append.php` in an extension (read when the extension is active).

Name

Default: `users`.

INI

```ini
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
Name=users
*/ ?>
```

Links

> The user tree, the Users tab's own page (its PolicyList[] and URL[default]; content.ini [NodeSettings] UserRootNode:
> a site with another user root node changes these two lines as it changes [Topmenu_users])

Default: a hash of 2: `accounts=content/view/full/5`, `sessions=setup/session`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "Links[]" first replaces the shipped list; without it the items are added
Links[]
Links[accounts]=content/view/full/5
Links[sessions]=setup/session
*/ ?>
```

LinkNames

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "LinkNames[]" first replaces the shipped list; without it the items are added
LinkNames[]
*/ ?>
```

PolicyList_accounts

Default: a list of 1: `5`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "PolicyList_accounts[]" first replaces the shipped list; without it the items are adde
d
PolicyList_accounts[]
PolicyList_accounts[]=5
*/ ?>
```

PolicyList_sessions

Default: a list of 1: `setup/administrate`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "PolicyList_sessions[]" first replaces the shipped list; without it the items are adde
d
PolicyList_sessions[]
PolicyList_sessions[]=setup/administrate
*/ ?>
```

Groups

Default: a list of 3: `users`, `access`, `account`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "Groups[]" first replaces the shipped list; without it the items are added
Groups[]
Groups[]=users
Groups[]=access
Groups[]=account
*/ ?>
```

GroupNames

Default: a hash of 3: `users=Users`, `access=Access control`, `account=My account`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "GroupNames[]" first replaces the shipped list; without it the items are added
GroupNames[]
GroupNames[users]=Users
GroupNames[access]=Access control
GroupNames[account]=My account
*/ ?>
```

GroupLinks_users

Default: a list of 2: `accounts`, `sessions`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "GroupLinks_users[]" first replaces the shipped list; without it the items are added
GroupLinks_users[]
GroupLinks_users[]=accounts
GroupLinks_users[]=sessions
*/ ?>
```

GroupSections

Default: a hash of 2: `access=Leftmenu_user`, `account=Leftmenu_my`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "GroupSections[]" first replaces the shipped list; without it the items are added
GroupSections[]
GroupSections[access]=Leftmenu_user
GroupSections[account]=Leftmenu_my
*/ ?>
```

LinkIcons

Default: a hash of 2: `accounts=people`, `sessions=person-check`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "LinkIcons[]" first replaces the shipped list; without it the items are added
LinkIcons[]
LinkIcons[accounts]=people
LinkIcons[sessions]=person-check
*/ ?>
```

LinkDescriptions

Default: a hash of 2: `accounts=Users and user groups; create and edit accounts.`, `sessions=Who is signed in; end sessions.`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "LinkDescriptions[]" first replaces the shipped list; without it the items are added
LinkDescriptions[]
LinkDescriptions[accounts]=Users and user groups; create and edit accounts.
LinkDescriptions[sessions]=Who is signed in; end sessions.
*/ ?>
```

MegaMenuLinks

Default: a list of 11: `accounts`, `sessions`, `access-roles_and_policies`, `access-unactivated`, `access-user_hygiene`, `access-user_audit`, `access-session_report`, `account-edit_profile`, `account-change_password`, `account-my_notifications`, `account-my_mail`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/menu.ini.append.php
[Leftmenu_user_mega]
# an empty "MegaMenuLinks[]" first replaces the shipped list; without it the items are added
MegaMenuLinks[]
MegaMenuLinks[]=accounts
MegaMenuLinks[]=sessions
MegaMenuLinks[]=access-roles_and_policies
MegaMenuLinks[]=access-unactivated
MegaMenuLinks[]=access-user_hygiene
MegaMenuLinks[]=access-user_audit
MegaMenuLinks[]=access-session_report
MegaMenuLinks[]=account-edit_profile
MegaMenuLinks[]=account-change_password
MegaMenuLinks[]=account-my_notifications
MegaMenuLinks[]=account-my_mail
*/ ?>
```

Related

- All blocks of menu.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/menu.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.