requestclassifier.ini [RuleSet-injection]

The settings of [RuleSet-injection] in requestclassifier.ini: Class, Patterns, Disabled

Source file: `doc/eng-us/examples/ini-settings/requestclassifier/RuleSet-injection.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/requestclassifier/RuleSet-injection.md

The block `[RuleSet-injection]` of `settings/requestclassifier.ini`, with 3 setting(s).

Never edit `settings/requestclassifier.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/requestclassifier.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/requestclassifier.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/requestclassifier.ini.append.php` in an extension (read when the extension is active).

Class

> Matched against the query and the path, decoded once; a posted body is never looked at.
> Rules: sql-union,
> sql-tautology (' or '1'='1), sql-boolean (or 1=1--), sql-time (sleep(, benchmark(),
> sql-schema
> (information_schema), sql-stacked (;drop table), sql-function, cmd-file (/etc/passwd),
> cmd-chain (;id, |cat, $(...),
> backticks), jndi, ssti ({{7*7}}, ${7*7}, #{...}, <%= %>), xss-script (<script, %3Cscript),
> xss-event (onerror=,
> <svg/on...), xss-url (javascript:), php-code.
> A search for "union station", O'Reilly, "select or drop" or **is no injection.**

Default: empty.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/requestclassifier.ini.append.php
[RuleSet-injection]
Class=
*/ ?>
```

Patterns

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/requestclassifier.ini.append.php
[RuleSet-injection]
# an empty "Patterns[]" first replaces the shipped list; without it the items are added
Patterns[]
*/ ?>
```

Disabled

Default: an empty list.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/requestclassifier.ini.append.php
[RuleSet-injection]
# an empty "Disabled[]" first replaces the shipped list; without it the items are added
Disabled[]
*/ ?>
```

Related

- All blocks of requestclassifier.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/requestclassifier.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.