setup.ini [open_basedir]

The settings of [open_basedir] in setup.ini:

Source file: `doc/eng-us/examples/ini-settings/setup/open_basedir.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/setup/open_basedir.md

The block `[open_basedir]` of `settings/setup.ini`, with 0 setting(s).

Never edit `settings/setup.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/setup.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/setup.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/setup.ini.append.php` in an extension (read when the extension is active).

Related

- All blocks of setup.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/setup.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.