site.ini [Cache]

The settings of [Cache] in site.ini: CacheItems

Source file: doc/eng-us/examples/ini-settings/site/Cache.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/site/Cache.md

The block `[Cache]` of `settings/site.ini`, with 1 setting(s).

Never edit `settings/site.ini` itself: an update replaces it. Put the settings you change in an override, which wins over the shipped file:

- `settings/override/site.ini.append.php` for every siteaccess,
- `settings/siteaccess/<siteaccess>/site.ini.append.php` for one siteaccess,
- `extension/<extension>/settings/site.ini.append.php` in an extension (read when the extension is active).

CacheItems

> Array with cache items to extend ezcache
> Example of use:
> CacheItems[]=custom
>
> [Cache_custom]
>
> [optional] Name of the cache item, key (custom) is used camel-cased if not set
> name=Custom cache
> [optional] Id of cache item, to be used from command line, key (custom) is used if not set
> id=custom
> [optional] If cache item should be cleared using cluster instead of plain file handler, def: false
> isClustered=true
> [optional] tags that will trigger clearing of this item, default: empty array
> tags[]=content
> tags[]=custom
> [optional] If cache uses eZExpiryHandler, then this is the key to get expiry time
> expiryKey=global-custom-cache
> [optional] (bool) If this cache is enabled or not, default: true
> enabled=false
> [optional] Path where cache is stored, either directory or file if class/purgeClass variables are unset, relative to current cache directory is assumed
> path=custom_cache.php
> [optional] custom cache clear function "<class>::clearCache()" to be called
> class=eZSomeClassName
> [optional] custom cache purge function "<class>::purgeCache()" to be called
> purgeClass=eZSomeClassName

Default: a list of 6: `rest`, `restRoutes`, `exphelpcontent`, `smarty`, `twig`, `searchsuggest`.

INI

```
<?php /* #?ini charset="utf-8"?
# settings/override/site.ini.append.php
[Cache]
# an empty "CacheItems[]" first replaces the shipped list; without it the items are added
CacheItems[]
CacheItems[]=rest
CacheItems[]=restRoutes
CacheItems[]=exphelpcontent
CacheItems[]=smarty
CacheItems[]=twig
CacheItems[]=searchsuggest
*/ ?>
```

Related

- All blocks of site.ini
- All INI files
- The settings page

Generated by `./console exp:help:examples` from `settings/site.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.