transform.ini

The blocks and settings of transform.ini.

Source file: `doc/eng-us/examples/ini-settings/transform/README.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/ini-settings/transform/README.md

The shipped settings of `settings/transform.ini`: 13 blocks, 35 settings.

> Exponential configuration file for character transformations
>
> NOTE: It is not recommended to edit this files directly, instead
> a file in override should be created for setting the
> values that is required for your site. Either create
> a file called settings/override/transform.ini.append or
> settings/override/transform.ini.append.php for more security
> in non-virtualhost modes (the .php file may already be present
> and can be used for this purpose).

Block	Settings
Transformation	5
Extensions	1
latin	2
cyrillic	2
greek	2
hebrew	2
search	3
urlalias_iri	3
urlalias	3
urlalias_compat	3
identifier	3
uppercase	3
lowercase	3

- All examples

Generated by `./console exp:help:examples` from `settings/transform.ini`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.