graphql (migration step)

Source file: doc/eng-us/examples/migration-steps/graphql.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/migration-steps/graphql.md

graphql

Runs a query or mutation of the GraphQL API in process as the run's user, and keeps its answer for references.

A step of a YAML migration with `type: graphql`. The class `expMigrationStepGraphql` (`kernel/classes/migration/steps/expmigrationstepgraphql.php`) is registered in `settings/migration.ini` `[StepSettings] StepTypeList[graphql]`.

Keys

Key	Type	Default	What it is
`persisted`	`string`		a persisted query: its name or its SHA-256
`query`	`string`		the text of the query or mutation
`file`	`string`		a .graphql file next to the migration
`variables`	`map`		the variables, name => value (references allowed)
`operation`	`string`		the operation to run when the text has several
`allow_errors`	`bool`	`false`	true: an answer with errors passes when it has data

Besides these, every step takes the keys of the engine: `type`, `mode`, `if`, `references`, `environments`, `engines` and `comment` (the file format). A key of type `identifier` names a node, an object or another part of the installation by id, remote id, path or name (identifiers).

Values for references

`references: { <name>: <value> }` keeps a value of the step's result as `${ref.<name>}` for the steps and migrations after it:

Value	What it is
`data`	the data of the answer (a map of the root fields)
`result`	the value of the first root field of the answer
`errors`	the messages of the errors (a list, empty when there were none)

Undoing

A step of this type does not undo itself: a migration with it needs `down:` or a rollback to its caption.

It touches no cache.

Example

YAML

```yaml
- type: graphql
  query: |
    mutation ($parent: Int!) {
      createContent(parentId: $parent, classIdentifier: "folder", fields: [ { identifier: "name",
 value: "News" } ]) { contentId nodeId }
    }
  variables: { parent: 2 }
  references: { news: result }
```

Related

- All step types
- YAML migration steps

Generated by `./console exp:help:examples` from `settings/migration.ini`, `kernel/classes/migration/steps/expmigrationstepgraphql.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.