sql (migration step)

Source file: doc/eng-us/examples/migration-steps/sql.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/migration-steps/sql.md

sql

Runs statements of the engine the installation runs on, written in the step or in files next to the migration.

A step of a YAML migration with `type: sql`. The class `expMigrationStepSql` (`kernel/classes/migration/steps/expmigrationstepsql.php`) is registered in `settings/migration.ini` `[StepSettings] StepTypeList[sql]`.

Keys

Key	Type	Default	What it is
`sql`	`string`		statements for every SQL engine (MySQL/MariaDB, PostgreSQL, SQLite, Oracle)
`mysql`	`string`		statements for MySQL/MariaDB (win over sql)
`postgresql`	`string`		statements for PostgreSQL (win over sql)
`sqlite`	`string`		statements for SQLite (win over sql)
`oracle`	`string`		statements for Oracle (win over sql)
`mongodb`	`list`		commands for MongoDB: insert, update, delete, create_collection, drop_collection, create_index, drop_index
`file`	`string`		a file next to the migration; the engine's own file (<name>.<engine>.sql, <name>.mongodb.json) wins over <name>.sql
`part`	`string`: up, down	`"up"`	the part of the file: up, or down (after a line "-- down")
`missing`	`string`: `fail`, `skip`	`"fail"`	what happens on an engine with no statements: fail or skip

Besides these, every step takes the keys of the engine: `type`, `mode`, `if`, `references`, `environments`, `engines` and `comment` (the file format). A key of type `identifier` names a node, an object or another part of the installation by id, remote id, path or name (identifiers).

Values for references

`references: { <name>: <value> }` keeps a value of the step's result as `${ref.<name>}` for the steps and migrations after it:

Value	What it is
`statements`	how many statements or commands ran
`engine`	the engine they ran on

Undoing

A step of this type does not undo itself: a migration with it needs `down:` or a rollback to its caption.

It touches no cache.

Example

YAML

```yaml
- type: sql
  sql: "UPDATE ezcontentclass SET always_available = 1 WHERE identifier = 'news';"
  mongodb:
    - { update: ezcontentclass, filter: { identifier: news }, set: { always_available: 1 } }
```

Related

- All step types
- YAML migration steps

Generated by `./console exp:help:examples` from `settings/migration.ini`, `kernel/classes/migration/steps/expmigrationstepsql.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.