The content module

The views of the content module: addresses, parameters and policy functions.

Source file: doc/eng-us/examples/module-views/content/README.md Last changed 2026-11-06
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/module-views/content/README.md

Name `eZContentObject`, defined in `kernel/content/module.php`. 51 views.

View	Address	Policy functions
action	/content/action	read
advancedsearch	/content/advancedsearch/<ViewMode>	read
bookmark	/content/bookmark	bookmark
browse	/content/browse/<NodeID>/<ObjectID>/<EditVersion>	read
collectedinfo	/content/collectedinfo/<NodeID>	read
collectinformation	/content/collectinformation	read
copy	/content/copy/<ObjectID>	read
copysubtree	/content/copysubtree/<NodeID>	create
dashboard	/content/dashboard	dashboard
download	/content/download/<ContentObjectID>/<ContentObjectAttributeID>	read
draft	/content/draft	edit
edit	/content/edit/<ObjectID>/<EditVersion>/<EditLanguage>/<FromLanguage>	edit or create
hide	/content/hide/<NodeID>	hide
history	/content/history/<ObjectID>/<EditVersion>	read or edit
job	/content/job/<JobID>	read
jobs	/content/jobs	read
keyword	/content/keyword/<Alphabet>	read
move	/content/move/<NodeID>	edit
multiedit	/content/multiedit	edit
new	/content/new	read
pdf	/content/pdf/<NodeID>	pdf
pendinglist	/content/pendinglist	pendinglist
queued	/content/queued/<ContentObjectID>/<version>	edit
removeassignment	/content/removeassignment	edit
removeeditversion	/content/removeeditversion	read
removemediaobject	/content/removemediaobject	read
removenode	/content/removenode/<ObjectID>/<EditVersion>/<EditLanguage>/<NodeID>	edit

View	Address	Policy functions
removeobject	/content/removeobject	read
removeuserobject	/content/removeuserobject	read
restore	/content/restore/<ObjectID>	restore
reverserelatedlist	/content/reverserelatedlist/<NodeID>	reverserelatedlist
search	/content/search	read
sharedpreview	/content/sharedpreview/<Token>	read
sitesuggest	/content/sitesuggest	read
subitemsexport	/content/subitemsexport/<NodeID>	read
suggest	/content/suggest	read
tipafriend	/content/tipafriend/<NodeID>	tipafriend; read
translation	/content/translation	read
translations	/content/translations/<TranslationID>	translations
trash	/content/trash	restore
treemenu	/content/treemenu/<NodeID>/<Modified>/<Expiry>/<Perm>	read
upload	/content/upload	create
urlalias	/content/urlalias/<NodeID>	edit
urlexport	/content/urlexport	urltranslator
urlimport	/content/urlimport	urltranslator_import
urlimporthistory	/content/urlimporthistory/<BatchID>	urltranslator_import
urlredirects	/content/urlredirects	urltranslator
urltranslator	/content/urltranslator	urltranslator
urlwildcards	/content/urlwildcards	urltranslator
versionview	/content/versionview/<ObjectID>/<EditVersion>/<LanguageCode>/<FromLanguage>	versionread
view	/content/view/<ViewMode>/<NodeID>	read

- The policies of this module
- All examples

Generated by `./console exp:help:examples` from `kernel/content/module.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.