/content/edit

The view content/edit: its address, parameters and the policy functions it needs.

Source file: doc/eng-us/examples/module-views/content/edit.md Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/module-views/content/edit.md

A view of the `content` module, defined in `kernel/content/module.php` and run by `kernel/content/edit.php`.

Address

```
/content/edit/<ObjectID>/<EditVersion>/<EditLanguage>/<FromLanguage>
```

Ordered parameters, in this order after the view name: `ObjectID`, `EditVersion`, `EditLanguage`, `FromLanguage`.

Who may open it

The user needs this policy function:

- `content/edit` or `content/create`

A policy on `content/*` (every function) also grants it; limitations of the policy (section, subtree, class ...) still apply where the view checks them.

Details

Key	Value
Navigation part	`ezcontentnavigationpart`
UI context	`edit`
Single POST actions	PreviewButton: Preview, TranslateButton: Translate, VersionsButton: VersionEdit, PublishButton: Publish, PublishNotNotifyButton: Publish, DiscardButton: Discard, BrowseNodeButton: BrowseForNodes, RemoveAssignmentButton: RemoveAssignments, EditLanguageButton: EditLanguage, FromLanguageButton: FromLanguage, TranslateLanguageButton: TranslateLanguage, BrowseObjectButton: BrowseForObjects, UploadFileRelationButton: UploadFileRelation, NewButton: NewObject, DeleteRelationButton: DeleteRelation, StoreButton: Store, StoreExitButton: StoreExit, MoveNodeID: MoveNode, RemoveNodeID: DeleteNode, ConfirmButton: ConfirmAssignmentDelete, SectionEditButton: SectionEdit, StateEditButton: StateEdit
POST actions	BrowseActionName
POST action parameters	EditLanguage (SelectedLanguage: EditSelectedLanguage), FromLanguage (FromLanguage: FromLanguage), TranslateLanguage (SelectedLanguage: EditSelectedLanguage), UploadFileRelation (UploadRelationLocation: UploadRelationLocationChoice), SectionEdit (RedirectRelativeURI: RedirectRelativeURI)

Example

A link in a template (`ezurl` adds the siteaccess and quotes the address); the parameter values are placeholders:

Template

```
<a href={'/content/edit/1/1/editlanguage/fromlanguage'|ezurl}>content/edit</a>
```

From PHP, the redirect a view gives after it has done its work:

PHP

```
return $Module->redirectTo( '/content/edit/1/1/editlanguage/fromlanguage' );
```

Related

- All views of content
- The policies of content
- A custom module and view

Generated by `./console exp:help:examples` from `kernel/content/module.php`, `kernel/content/edit.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.