The oauthadmin module

The views of the oauthadmin module: addresses, parameters and policy functions.

Source file: `doc/eng-us/examples/module-views/oauthadmin/README.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/module-views/oauthadmin/README.md

Name `Rest client admin`, defined in `kernel/private/modules/oauthadmin/module.php`. 6 views.

View	Address	Policy functions
action	`/oauthadmin/action`	(module)
edit	`/oauthadmin/edit/<ApplicationID>`	(module)
keyaction	`/oauthadmin/keyaction`	(module)
keys	`/oauthadmin/keys`	(module)
list	`/oauthadmin/list`	(module)
view	`/oauthadmin/view/<ApplicationID>`	(module)

- The policies of this module
- All examples

Generated by `./console exp:help:examples` from `kernel/private/modules/oauthadmin/module.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.