false template operator

The false template operator: no named parameters, registered by eZTemplateLogicOperator.

Source file: `doc/eng-us/examples/template-operators/false.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/template-operators/false.md

The false template operator

Registered in `lib/eztemplate/classes/eztemplateautoload.php` by the class `eZTemplateLogicOperator` (`lib/eztemplate/classes/eztemplatelogicoperator.php`). The same class also registers: lt, gt, le, ge, eq, ne, null, not, true, or, and, choose.

Parameters

None.

The operator takes no input: it is called on its own, not after `|`.

Example

Built from the parameter list above; the values are placeholders (the operator's template hints decide whether it takes an input).

Template

```
{false}
```

In a shipped template

The first use in the templates of this installation, `design/admin/templates/children_detailed.tpl` line 198:

Template

```
{def $group_id = false()}
```

Related

- All template operators
- Templates and design
- A custom template operator

Generated by `./console exp:help:examples` from `lib/eztemplate/classes/eztemplateautoload.php`, `lib/eztemplate/classes/eztemplatelogicoperator.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.