node_encode template operator

The node_encode template operator: 3 parameter(s), registered by ezjscEncodingTemplateFunctions.

Source file: `doc/eng-us/examples/template-operators/node_encode.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/template-operators/node_encode.md

The node_encode template operator

Registered in `extension/ezjscore/autoloads/eztemplateautoload.php` by the class `ezjscEncodingTemplateFunctions` (`extension/ezjscore/autoloads/ezjscencodingtemplatefunctions.php`). The same class also registers: json_encode, xml_encode.

Parameters

Parameter	Type	Required	Default
node	object	yes	array()
params	hash	no	array()
type	string	no	'json'

Example

Built from the parameter list above; the values are placeholders (the operator's template hints decide whether it takes an input).

Template

```
{$value|node_encode( $node, hash(), 'json' )}
```

Related

- All template operators
- Templates and design
- A custom template operator

Generated by `./console exp:help:examples` from `extension/ezjscore/autoloads/eztemplateautoload.php`, `extension/ezjscore/autoloads/ezjscencodingtemplatefunctions.php`. Do not edit this page: change the source and generate again (how). Free documentation: GFDL 1.3 or later.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.