Template-Operator xml_encode

Der Template-Operator xml_encode: 1 Parameter, registriert von ezjscEncodingTemplateFunctions.

Source file: `doc/ger-de/beispiele/template-operatoren/xml_encode.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/examples/template-operators/xml_encode.md

Der Template-Operator xml_encode

Registriert in `extension/ezjscore/autoloads/eztemplateautoload.php` von der Klasse `ezjscEncodingTemplateFunctions` (`extension/ezjscore/autoloads/ezjscencodingtemplatefunctions.php`). Dieselbe Klasse registriert auch: json_encode, node_encode.

Parameter

Parameter	Typ	Erforderlich	Standard
hash	hash	ja	`array()`

Beispiel

Aus der Parameterliste oben gebildet; die Werte sind Platzhalter (die Template-Hinweise des Operators entscheiden, ob er eine Eingabe nimmt).

Template

```
{$value|xml_encode( hash() )}
```

Siehe auch

- Alle Template-Operatoren
- Templates und Design
- Ein eigener Template-Operator

Erzeugt von `./console exp:help:examples --language=ger-de` aus `extension/ezjscore/autoloads/eztemplateautoload.php`, `extension/ezjscore/autoloads/ezjscencodingtemplatefunctions.php`. Bearbeiten Sie diese Seite nicht: Ändern Sie die Quelle oder die deutsche Übersetzung und erzeugen Sie sie neu (wie). Freie Dokumentation: GFDL 1.3 oder später.

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.