New parameter in 'content_structure_tree' operator

Added new boolean parameter in 'content_structure_tree' operator: $unfoldNodeID.

Source file: doc/eng-us/features/3.6/content_structure_tree_operator_changes.txt Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/features/3.6/content_structure_tree_operator_changes.txt

```
*Title: New parameter in 'content_structure_tree' operator.

*Documentation:
Added new boolean parameter in 'content_structure_tree' operator: $unfoldNodeID.
<code>
{set contentStructureTree = content_structure_tree( $rootNodeID, $classFilter,
                                                    $maxDepth, $maxNodes,
                                                    $sortBy, $fetchHidden,
                                                    $unfoldNodeID ) }
</code>

If $unfoldNodeID is not set or equal 0 (false) then 'content_structure_operator'
works as it worked before. Otherwise, $unfoldNodeID define a node which must be
unfolded. Note what node (defined by the $unfoldNodeID) can be only first-level
child of the root node (defined by the $rootNodeID). If node $unfoldNodeID is
not first-level child of the root node or cannot be fetched att all then
'content_structure_tree' operator works as it worked before too.
```

Copyright (C) 1999 - 2014 eZ Systems AS and contributors
This page was inherited from the documentation of the original software and is not covered by the GNU Free Documentation License. It is distributed under the GNU General Public License, version 2 (https://www.gnu.org/licenses/old-licenses/gpl-2.0.html).