The expui JavaScript API

A reference card of Exponential UI, the admin's JavaScript library: packer keys, exp_config(), the Exp core, Exp.io server calls, dialogs, tables, date pickers, uploads and toolbars.

Source file: `doc/eng-us/help/extension-development/part-8-reference/expui-javascript-api.md` Last changed 2026-11-04
https://doc.exponential.earth/learninminutes/exphelp/viewer/help/extension-development/part-8-reference/expui-javascript-api.md

Part 8, reference 30. Exponential UI (the extension `expui`, object `Exp` in the browser) is the JavaScript library of the administration since YUI was removed. Extensions use it for their admin pages. This page summarizes its API documentation (`doc/API.md` of the expui repository, version 1.0.0.1 at the time of writing); the full description of each module is in its `doc/modules/` folder. Moving old YUI code to it is in From YUI to expui.

Loading

Template call	Loads
`{exp_config( hash( 'prefs', array( ... ), 'strings', array( ... ) ) )}`	the page's configuration block: preferences and translated texts for your script
`{ezscript_require( 'exp::core' )}`	jQuery 4 and the core
`{ezscript_require( array( 'exp::core', 'exp::io' ) )}`	and the server calls
`{ezcss_require( 'exp/core.css' )}`	the design tokens (`--exp-*`) and utilities

Module keys: `exp::collapse`, `exp::sticky`, `exp::dialog`, `exp::upload`, `exp::datatable`, `exp::datepicker`, `exp::autosave`, each with its stylesheet `exp/<module>.css`. **The admin designs load all of them on every page**, so an admin page of your extension usually needs only its own script.

The core (Exp)

API	Does
`Exp.ready( fn )`	run when the page is ready
`Exp.i18n( text, params )`	a text from the `strings` of `exp_config()`
`Exp.on( name, fn )`, `Exp.off( name, fn )`, `Exp.emit( name, data )`	page-wide events; prefix your names (`myext:saved`)
`Exp.register( name, init )`, `Exp.start( root, only )`	start behavior from HTML (`data-*` markup)
`Exp.prefs.get( name, fallback )`, `Exp.prefs.set( name, value )`	user preferences
`Exp.keys.bind( combo, fn, options )`	keyboard shortcuts
`Exp.token()`	the page's form token
`Exp.reducedMotion`	`true` when the user asked for less motion

Server calls (Exp.io)

API	Does
`Exp.io.call( fn, args, options )`	an ezjscore server function; POST by default; returns a Promise with the function's content, rejects with an `Exp.io.Error`
`Exp.io.form( form, options )`	post a form with its files, adding the form token
`Exp.io.poll( fn, args, options )`	call again every every ms until `until( content )` is true
`Exp.io.url( path )`	the address of a path in the current siteaccess

JavaScript

```
Exp.io.call( 'myext::items', [ 2 ], { method: 'GET' } ).then( function ( items ) {
    // use items
}, function ( error ) {
    // error.kind: signedout, refused, server, network, timeout, invalid
} );
```

Modules

Module	API
`exp::dialog`	`Exp.dialog.open( options )`, `confirm( text )`, `alert( text )`, `form( url, options )`, `create( options )`; markup `data-exp-dialog`
`exp::datatable`	`$( el ).expDataTable( options )`; markup `data-exp-datatable`
`exp::datepicker`	`$( el ).expDatePicker( options )`; `window.showDatePicker()`
`exp::upload`	`$( el ).expUpload( options )`; markup `data-exp-upload`
`exp::collapse`	`Exp.collapse( conf )`, `$( el ).expCollapse( conf )`
`exp::sticky`	`$( toolbar ).expSticky( options )`, `Exp.sticky.start( toolbar, options )`
`exp::autosave`	`new Exp.autosave.AutoSubmit( conf )`, `$( form ).expAutosave( conf )`, `$( el ).expPreview( conf )`

All dialogs return Promises and use the browser's own `<dialog>` element.

Under a Content Security Policy

Exponential UI is loaded from files, and its modules start from `data-*` markup, so a page built with it needs no inline script (CSP: moving inline scripts into files). Pass your page's texts through `exp_config()` rather than an inline script.

Related pages

- Previous: Error codes and module results
- Next: admin4 components and tokens
- ezjscore server functions reference

- YUI removed from Exponential
- Free documentation: this page is free to copy, translate and improve under the GNU FDL 1.3.

Become an Exponential Partner

Partners share their information, provide funding, contribute back and develop the products with us, and that is how Exponential grows. A partner website and dashboard are planned for mid-2027: please become a partner today to speed up our growth rate and land new features faster.

Partners: start here | How to apply

Exponential Copyright © 1998-2026 Exponential Foundation and 7x
Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".
This documentation is free documentation, licensed under the GNU Free Documentation License 1.3 or later:
https://www.gnu.org/licenses/fdl-1.3.html.